

C2、C3 按钮开关 Pushbutton Switch



规格 Specifications

电气容量 Electrical capacitor	最大绝缘电压 600VAC, 最大热电流 10A Max insulation voltage 600VAC, Max thermal current 10A
操作类别 Operation	AC15 类: 250VAC/6A, DC13 类: 250VDC/0.6A AC15 Type: 250VAC/16A, DC13 Type: 250VDC/0.6A
触点导阻 Contact resistance	最大 50MΩ Max 50MΩ
绝缘强度 Insulation strength	2500VAC 50Hz, 1 分钟 2500VAC 50Hz, 1 minute
绝缘阻抗 Insulation resistance	500VDC 下, 大于 100MΩ 500VDC below, 100MΩ above
耐震阻值 Vibration resistance	10g @40-500Hz
用灯寿命 Life	白炽灯 1,000 小时, LED 灯 100,000 小时 Lamp 1,000hour, LED 1,000hour
电气寿命 Electrical life	开关片 AC15 250VAC/6A >1, 000, 000 Contact block AC15 250VAC/6A >1, 000, 000 DC13 250VAC/0.6A >1, 000, 000 DC13 250VAC/0.6A >1, 000, 000
储存温度 Storage temperature	使用时 -20~+70℃ (没有结冰) Using: -20~+70℃ (With no icing)
操作室温 Operation temperature	使用时 -20~+70℃ (没有结冰) Using: -20~+70℃ (With no icing)

型号说明 Model Number Structure



① 固定孔径: C2=22 φ Round, C3=30 φ Round

② 型式:

SNS= 短柄旋钮, SNL= 长柄旋钮
SNK= 钥匙旋钮, PNF= 平头按钮, PNH= 凸头按钮
PNM3=30mm 大头按钮, PNM4=40mm 大头按钮
PNM6=60mm 大头按钮, PNR3=30mm 急停按钮
PNR4=40mm 大头按钮, PNR6=60mm 急停按钮,
PNKM4= 急停钥匙旋钮, PND= 双位带灯按钮
PNP= 拉伸开关, PIF= 平头带灯按钮
PIH= 凸头带灯按钮, PIM4= 大头带灯按钮
PID= 双位按钮, SIS= 短柄带灯按钮
SIL= 长柄带灯按钮, LIF= 标准型指示灯
LUF= 圆型指示灯, MN= 十字开关

③ 操作型式: 按钮开关 空白= 自复位, D= 自锁式
旋钮开关, 十字开关: F2=2 向自锁, F3=3 向自锁,
F4=4 向自锁, T2=2 向复位, T3=3 向复位, T4=4 向复位

④ 接点: 1A=1NO, 1B=1NC, 1C=1A1B, 1D=1A+1B
2A=2NO, 2B=2NC, 2C=1A1B+1A1B

⑤ 头部颜色: R= 红, G= 绿, Y= 黄, W= 白, B= 黑, BL= 蓝

⑥ 带灯电压: 12=12VDC, 24=24VDC, 36=36VDC, 48=48VDC
110=110VAC, 220=220VAC, 380=380VAC

① Fixed hole diameter: 2=22 φ Round, 3=30 φ Round

② Types:

SNS=Short handle knob, SNL=Long handle knob
SNK=key knob, PNF=flat head, PNH=convex head
PNM3=30mm big head, PNM4=40mm big head
PNM6=60mm big head, PNR3=30mm Emergency stop head
PNR4=40mm big head, PNR6=60mm Emergency stop head,
PNKM4=Emergency stop knob, PND=Double with lamp button
PNP=Tensile switch, PIF=Flat ribbon lamp button
PIH=Convex head with lamp button, PIM4=big head with lamp button,
PID= Double button, SIS=Short shank with lamp knob
SIS=Long handle with lamp knob, LIF=Standard type indicating lamp
LUF=circular type indicating lamp, MN=Monolever Switch

③ Operation type: Pushbutton Switch: Blank=Self-resetting, D=Self-locking
Knob Switch, Monolever Switch: F2=2 to the self-locking, F3=3 to the self-locking,
F4=4 to the self-locking, T2=2 to reset, T3=3 to reset, T4=4 to reset

④ Contact: 1A=1NO, 1B=1NC, 1C=1A1B, 1D=1A+1B
2A=2NO, 2B=2NC, 2C=1A1B+1A1B

⑤ Head color: R=red, G=green, Y=yellow, W=white, B=black, BL=blue

⑥ With lamp voltage: 12=12VDC, 24=24VDC, 36=36VDC, 48=48VDC
110=110VAC, 220=220VAC, 380=380VAC

注: 定制产品在以上选型不能解释清楚的, 定货时请另外注明。
Note: Custom products over the selection can not explain clearly, please also
specify when ordering.