

Physical Parameter	
Type	Fixed Wide Barcode Scanner Module
Material	ABS +PC
Color	Black
Power Supply	DC 5V ±5%
Weight	50±5g (Without the cable)
Performance Parameter	
Interface	USB, RS-232
Sensor	Planar CMOS sensor
Light Source	Red CCD(aiming) ,white LED (lighting)
Professor	32-bit MCU
Decoding Capability	1D:Codabar,Code11,Code39/Code93,UPC/EAN,Code128/EAN128,InterLeaved2of5,Matrix2of5,MSI CODE,Standard2of5. 2D:QR CODE ,PDF417 ,Data Matrix
Resolution	Code39 5mil, QR 8.7mil, PCS45%
Scanning Depth	5MIL CODE39: 5--12 CM 15MIL CODE39 : 4--25 CM 10MIL CODE93 : 4--21 CM 15MIL UPC/EAN: 4--25 CM 20MIL QR : 4--25 CM
Trigger Mode	Manual, Automatic induction, Continuous scanning
Scanning Width	5 * 5 cm ² -- 30 * 30 cm ²
Prompt Mode	Buzzer, Indicator Light(LED)
Print Contrast	Min 35%
Scanning Angle	Roll35°,Pitch65°,Yaw65°
Environment Parameter	
Operating Temp.	0 to 50 °C / 32 to 122 °F
Storage Temp.	0 to 50 °C / 32 to 122 °F
Operating Humidity	5 - 95% (No Condensation)
IP Grade	≥IP54
ESD Protection	15kv
Shock Resistance	1.5m free fall on concrete surface