



Pin NO.	Pin Name
1	VSS
2	VDD
3	VLCD
4	RS
5	R/W
6	E
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	LED(+)
16	LED(-)
Interface	6800

**SPECIFICATIONS:**

- 1.DISPLAY TYPE:YELLOW-GREEN/STN
- 2.VIEWING DIRECTION:6:00 O'CLOCK
- 3.POLARIZER MODE:TRANSELECTIVE/POSITIVE
- 4.DRIVE METHOD:1/16 DUTY,1/5 BIAS
- 5.OPERATING TEMP:-20°C---+70°C
- 6.STORAGE TEMP:-30°C---+80°C
- 7.WORKING VOLTAGE:VDD-VSS=+5.0VDC
- 8.BACKLIGHT:YELLOW-GREEN
- 9.ALL UNMARKED TOLERANCES:±0.20mm/±0.5°



**深圳市佳显电子技术有限公司**  
Shenzhen Goodview Electronic Technology Co.,Ltd



绘图: 李建清 Drawn by: 李建清	绘图编号: LCM-SJXD1604ADYSYMN Drawing No.:	单位: mm
审核: 李建清 Checked by: 李建清	客户编号: 1604ADYSYMN Customer No.:	日期: 2024-08-06 Date:
批准: 李建清 Approved by: 李建清	图纸版号: V1 Drawing Version:	页数: 1/1 Sheet No.:

版本 Ver.	标记 Mark	更改内容 Modify the content	更改人 Modified by	日期 Date	版本 Ver.	标记 Mark	更改内容 Modify the content	更改人 Modified by	日期 Date
					V1		First issue	李建清	20240806