

Model			YSAF-09HRDN8	YSAF-12HRDN8	YSAF-18HRDN8	YSAF-24HRDN8
Power supply	Ph-V-Hz		220V-240V,1Ph,50Hz	220V-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz
Rated Cooling	Btu/h		9000(3100~10600)	12000(3800~14200)	18000(6200~20900)	24000(7100~27120)
Cooling Power input	W		710(100~1240)	1237(130~1580)	1921(140~2360)	2345(160~2960)
Cooling Current	A		3.1(0.4~5.4)	5.37(0.5~6.9)	8.4(0.6~10.3)	10.2(0.7~13.3)
Rated Heating	Btu/h		10000(2800~11500)	11000(3700~144000)	19000(4700~23000)	25000(5500~30000)
Heating Power input	W		739(120~1200)	964(100~1580)	1546(200~2410)	2035(260~3140)
Heating Current	A		3.2(0.5~5.2)	4.19(0.4~6.9)	6.7(0.9~10.5)	10.2(1.1~13.3)
Seasonal Cooling	Pdesignc	kW	2.6	3.5	5.2	7.0
	SEER	W/W	6.2	6.1	7.1	6.1
	Energy Efficiency Class		A++	A++	A++	A++
Heating(Average)	Pdesignh	kW	2.1	2.3	4.1	4.8
	SCOP	W/W	4	4	4	4
	Energy Efficiency Class		A+	A+	A+	A+
	Tbiv	℃	-7	-7	-7	-15
Heating(Warmer)	Pdesignh	kW	2.6	2.7	4.5	6.4
	SCOP	W/W	4.9	4.6	5.2	5
	Energy Efficiency Class		A++	A++	A+++	A++
	Tbiv	℃	2	2	2	2
Compressor	Type		ROTARY	ROTARY	ROTARY	ROTARY
	Brand		GMCC	GMCC	GMCC	GMCC
Indoor unit	Dimension(W*D*H)	mm	805x194x285	805x194x285	957x213x302	1040x220x327
	Packing (W*D*H)	mm	870x270x360	870x270x360	1035x295x380	1120x405x310
	Net/Gross weight	Kg	7.5/9.7	7.5/9.7	10/13	12.3/15.8
Outdoor unit	Dimension(W*D*H)	mm	700x275x550	700x275x550	800x333x554	845x363x702
	Packing (W*D*H)	mm	815x325x615	815x325x615	920x390x615	965x395x765
	Net/Gross weight	Kg	22.7/25.2	22.7/25.2	34/36.7	51.5/54.5
Refrigerant	Type		R32	R32	R32	R32
Thermostat type			Remote Control	Remote Control	Remote Control	Remote Control
Application area (Cooling Standard)	m2		12-18	16-23	24-35	32-47
Qty'per 20' /40' /40'HQ			114/235/278	114/235/278	78/168/188	64/136/146