




HIGH TEMP. WIRE CONNECTORS

Features

- UL 486C Listed and CSA 22.2 No. 188 Certified.
- Thermoplastic shell designed to withstand extreme temperatures.
- Temperature rated to 150°C (302°F)
- Rated at 600 V Max. for building wiring and 1000 V Max. in lighting fixtures/luminaries and signs.
- Available in two standard models.
- Available in socket tools for easy installation of connectors (See page 9).



Dimensions

Model	A		B		C		D		E	
	mm	in.	mm	in.	mm	in.	mm	in.	mm	in.
P1B	3.80	0.150	6.50	0.256	8.60	0.339	5.80	0.228	15.20	0.598
P3B	5.00	0.197	9.70	0.382	12.70	0.500	7.80	0.307	22.00	0.866

Ratings

Model	Color	Elec. Rating & Wire Range	Approval			Packing	Cat. No.
P1B	Black	300 V Max. Temp. 150°C (302°F) No. 22 - No. 18 AWG Max. 2 #18 Str Min. 1 #18 Str w/1 #22 Str				Ctn of 20,000 (20 plastic bags, 1,000 ea)	P1B01
P3B	Black	600 V Max. Temp. 150°C (302°F) No. 22 - No. 14 AWG Max. 1 #14 w/1 #16 w/1 #18 Min. 1 #16 w/1 #22				Ctn of 5,000 (10 plastic bags, 500 ea)	P3B01