



- LED

High luminous efficiency COB LED
- Power supply

Flickering free power supply, short circuit and over voltage protection
- Optics

Low glare optic system with PC lens
- Installation

Recessed



Model No.	DSDLR4001-5W	DSDLR6001-10W	DSDLR7501-15W
-----------	--------------	---------------	---------------

Electrical data			
Power	5W	10W	15W
Input voltage	200-220V AC or 120-277V AC		
Main frequency	50/60Hz		
Power factor	>0.9		
Total harmonic distortion	<10%		
Photometrical data			
Luminous flux	600lm	1200lm	1800lm
Luminous efficiency	120lm/W		
Color temperature	3 CCT		
CRI	>80		
Beam angle	15°, 24°, 36°		
Material			
Optic material	PC		
Housing material	Aluminum		
Product surface finishing	Powder coating		
Application			
Operating temperature	-40°~ +60°		
Operating humidity	10%-90%		
IP rate	IP20		
Application environment	Indoor		
Dimmable	Optional		
Lifespan & Warranty	Lifetime up to 50000H, 5 years warranty		

Dimension & Color									
Dimension symbol	a	b	c	a	b	c	a	b	c
Dimension (mm)	40	58	35	60	83	55	75	95	65
Color option									
				satin black RAL9005			satin white RAL9003		