

1D Handfree Barcode Scanner XL-6500A



- ⊗ Rugged and stylish design.
- ⊗ Quick and fluent reading performance.
- ⊗ Laser scanner with auto scan and bracket.
- ⊗ Bracket disassembled to saving shipping cost.
- ⊗ With IP54 waterproof and dustproof protection.



Model Number	XL-6500A	Size	L × W × H:175mm × 73mm × 102mm
Light Source	Visible Laser Diode 650nm	Weight	246g
Scan Pattern	Single Scan	Material	ABS+PC
Decode Rate	300 times/second	Voltage	5VDC
Scan Precision	3mil	Operating Current	85mA
Scan Width	30mm@scan window, 220mm@200mm	Static Current	30mA
Scan Depth of field	0-330mm (0.33mm pcs0.9)	Laser Class	Meet the Grade I National Criteria for Laser Safety
Elevation Angle	65	EMC	CE& FCC DOC compliance
Deflection Angle	55	Operating Temperature	- 0°C to 50°C
Support Interface	PS-2(KB); RS-232; USB-HID; USB-Virtual COM	Storage Temperature	- 40°C to 70°C
Print Contrast	10% UPC/EAN 100%	Humidity	5% to 85% relative humidity,non-condensing
Mention Pattern	Buzzer, Indicator	Light Levels	Daylight,3000-8000LUX
Scan Mode	Manual	Shock	Designed to withstand 1.5M drops
Decoding Capability	EAN-8/EAN-13/UPC-A/UPC-E/Code 39/Code 93/Code 128/EAN128/Codabar/Industial 2 of 5/Interleave 2 of 5/Matrix 2 of 5/MSI.		



SUNLUX IOT Technology (Guangdong) Inc.

Office Add: 4F,No.7 ,Kehui First Street ,Science Road,Science City,Guangzhou,China

Tel: +86-20-32053765 Fax: +86-20-82115390 Site: www.xl-scan.com E-mail: sales@xl-scan.com