

Specification

Outlook	Model	H511C Mini Hunting CAM
   	Highlight	◆1 Mega pixels Digital Camera ◆720P video ◆16 months Standby time ◆20m range of IR flash ◆Triggering time: 0.45 Second ◆25m triggering distance ◆Spray-water protected(IP protection class66)
	Image sensor	1Mega pixels Digital Camera
	Still image size	12MP:4000x3000;8M:3264x2448(interpolated);5M:2592x1944(interpolated);3M:2048*1536; 1M:1280*960
	Video clip	1920x1080/25fps; 1280x720/30fps; 720x480/30fps; 640x480/30fps;320x240/30fps
	File format	JPG/AVI
	Lens angle	f=3.62mm; F/NO2.2; FOV=70°; Auto IR filter
	LCD Display	2.0"TFT 128*160
	Memory	External memory(TF card, Class 6 Above, up to 32GB) / Internal memory(8Mx16 SDRAM)
	Operation keypad	6 Keys
	The number of IR lamp	2PCS (High power /850nm)
	Range of IR flash	20m
	Triggering distance	25m (Below 77°F/25°C at the Normal Level)
	Prep PIR sensing angle	60°
	Triggering time	0.45 Second(When using the 4G SD card);
	Trigger interval	5sec. - 60min;Programmable
	Shooting numbers	1--3;
	Video Length	3sec-10Minutes.; Programmable
	Effectiveness	Daytime:1m-infinite;Night time:1.5m-20m
	Camera+Video	First take Picture then Video
	Time stamp	On/Off;Include serial No.,temperatureand moon phase
	Time lapse	On/Off; Time Lapse Programmable
	Compressed video	TL Video Time Laps 3 Second ~ 24Hours
	Periodic Shot	Time Laps 1 Second ~ 24Hours
	Device serial No.	4 digits or 26 alphabets set by yourself
	Build-in Micophone/Speaker	Yes
	Auto-distinguish images	Color images in daytime/black & white night images
	Automatic screen saver	Automatic screen saver in 2 minutes while no keypad controlling
	PC interface	Mini USB2.0
	Power supply	4xAA;, external 6V power supply,at least 2A
	Standby time	approx.12 months
	Lockable	Optional
	Password protection	4-Digit Numbers
	Spray-water protected	Spray-water protected
	Operating temperature	-7℃ to +40℃
	Storage Temperature	-20℃ to +60℃
	Dimensions & Weight	104*75*43mm