

Specification

1.Cat5e keystone jack
2.Meet TIA/EIA-568-A and TIA/EIA-568-B Category5E requirements
3.Meet TIA/EIA TSB-40
4.Meet ISO/IEC Generic Cabling Standard 11801
5.Meet CENELEC Generic Cabling Standard EN50173
6.Angle: 180 Degree or 90 Degree
7.Termination: Krone- 110- DUAL Type

Electrical

1.According to UL 1863	
2.Voltage rating:	150 Volts
3.Current Rating :	1.5AMP
4.Contact resistance:	20 m-ohm
5.Insulation Resistance:	500M-ohm
6.Dielectric Withstand Voltage:	1000 V AC RMS, 60Hz 1min

Environment

1.Storage:	-40~ 85°c
2.Operation:	0~70°c
3.Housing Material:	PBT-UL90V-0

Machanical

1.Panel Frame:	Carbon Steel, Powder Coating in black color
2.Contact Material:	PC-UL90V-0
3.Contact:	PC UI94V-0, 0.45mm(0.018") Diameter Phosphor bronze with 3 U" to 50 U" Gold plating on contact area.
4.RJ45 Jack Life	750 times MIN.
5.Insertion Life:	≥ 1000 Mating Cycles
6.IDC:	PC UL94V-0, Accept 22-26 AWG Solid Wire.
7.Tia Cat.5e Perm Link Test:	Worst Pair NEXT Margin ≥3dB
8.Retentiveness of insertion structure:	50N 60±5s
9.PCB:	FR4 1.6mm(0.04") thickness, 2 layers

Packing

1PC	PE Bag
100PCS	White Box
1000PCS	Carton
Carton Size	42*26*45cm
Carton G.W	10KG

Shipping

Delivery Methods	By UPS/DHL/TNT/ FEDEX/ , By Air/Sea
Leading time	10-20 days

Our Service

OEM & Netural	Logo can engrave or silk print or laser print on Products ; Can redesign the mold as your requirement
Samples	Provide in 3 days
Quality	Guarante 5 years
After sales Service	Provide professional & fast service if you have problem

What is our payment options?

They can be T/T, L/C, Western Union, Paypal or others by negotiation!

Do we manufacture products with our own facility?

Yes, that is reason why our products have the absolute advantage in the market!

Can we customize special products?

Yes, we will be happy to satisfy every requirement from our customers!