

1D Omini-directional Module

XL-200



- ☉With CE, FCC certificates.
- ☉Firmware update online with USB cable.
- ☉Support USB, PS2 and RS-232 interfaces.
- ☉Intelligent and cubic design for easy integration.
- ☉32 bit CPU with superior scanning performance.



Model Number	XL-200	Scan Mode	Automatic
CPU	32 Bit ARM	Size	L x W x H: 58mm x 64mm x 44mm
Light Source	Visible Laser Diode 650nm	Weight	101g
Scan Pattern	20 lines 5 fields of 4 parallel lines	Material	ABS + PC
Scan Rate	1500 scans/second	Voltage	DC 5V
Scan Precision	5mil@PCS90%	Operating Current	1.0Watt
Scan Width	0-220mm for 0.33mm UPC/EAN 100%	Static Current	220 mA
Scan Depth of Field	0-216mm for 0.33mm UPC/EAN 100%	Laser Class	Meet the Grade I National Criteria for Laser Safety
Interface	USB, RS232, Keyboard Wedge	EMC	CE & FCC DOC compliance
Print Contrast	30% @ UPC/EAN 100%	Humidity	5% to 85% relative humidity
Mention Pattern	Buzzer	Shock	Designed to 1.5M drops
Decoding Capability	UPC/EAN/JAN, UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39 (with full ASCII), Codabar (NW7), Code 128 & EAN 128, Code 93, Interleaved 2 of 5 (ITF), Addendum 2 of 5, IATA Code, MSI/Plessey, Code 32 (Italian Pharmacode), RSS 14, RSS Limited, RSS Expanded, China post.		



SUNLUX IOT Technology (Guangdong) Inc.

Office Add: 4F, No.7, Kehui First Street, Science Road, Science City, Guangzhou, China

Tel: +86-20-32053765 Fax: +86-20-82115390 Site: www.xl-scan.com E-mail: sales@xl-scan.com