


<b>Model</b>	<b>M20X</b>
<b>Picture</b>	
<b>Brand OEM</b>	
maximum speed limit	20 mph / 32 km/h
color	Black
Range (dependent upon usage, weather, conditions, terrain and rider's total weight)	pure electric : 30 km -40km / 18-25mile pedal assist : 40- 60Km / 25 - 40 mile (measured at a constant speed of 20km/h on a flat asphalt road with a weight of 75kg without wind at 25°C)
Battery	48V 10AH Lithium Battery Plastic Case (13S4P)
Batteries	CHINA 18650 power cell
meter	LCD display speed and battery
Climbing gradient	11° (rider weighs 220.4 lb. / 100kg)
riding road	Cement, asphalt pavement, flat dirt pavement, no higher than 5cm steps, no more than 3cm wide trenches
drive mode	rear drive
Brake method (brake lever)	Front wheel disc brake (left brake lever) + rear wheel disc brake (right brake lever)
braking distance	22km/h speed 1. The braking distance of single brake is less than or equal to 7m in dry state 2.Double brake Braking distance in dry state ≤4.4m
Charger	Output: 54V, 2A Input: 100-240V, 50/60Hz
charging time	Fully charged in about 5-6 hours
Charging temperature range	Available 32°F-104°F / 0°C-40°C
Nominal load	≤120kg
headlight	Available
taillight	LED tail lights (The running light is on when it is turned on, and the brake light is on when braking)
trumpet	none
frame	High-carbon steel
front wheel	Driven wheel 20"4.0 (spoke hub) Pneumatic tire 160mm brake disc
rear wheel	48V 500W drive wheel 20"4.0 pneumatic tire 160 brake disc
tire	20 inch * 4.0
Damping system	Front absorption
Operating temperature	-4°F-140 °F /-20°C-60°C
Storage temperature	Available (-20~40°C)
maximum storage time	Factory state (70% battery) ~180days Battery exhausted state <120days It is recommended to recharge at least every 60 days
wheelbase	1040 mm
Whether to fold	not collapsible
Vehicle size L×W×H	64"30"43 Inch /1620mm×760mm×1080mm
Vehicle protection level	IPx4
charger	External 48V 2A
packaging parts (Assembly degree)	95%
Outer box material	ABC corrugated 7 layers
Outer box pattern	simple
Package dimensions	64.5"9.85 *36.6 inch / 1640mm *250mm*930mm
Packaging buffer material	EPS
net weight	77lbs / 35KG
Gross Weight (Approx.)	88lbs /40KG
20GP(28cbm)	80
40GP(58cbm)	175
40HQ (68CBM)	195