

Model	HP-570C-APP	
	Range	Accuracy
DC Voltage	400mV/4V/40V/400V	\pm (0.5% of rdg+2 digits)
	1000V	\pm (0.8% of rdg+2 digits)
AC Voltage	4V/40V/400V	\pm (3.0% of rdg+10 digits)
	750V	\pm (1.2% of rdg+3 digits)
		\pm (2.5% of rdg+5 digits)
DC Current	200A	\pm (3.0% of rdg+10 digits)
	1000A 0~800	\pm (3.5% of rdg+10 digits)
	800~1000	\pm (6.5% of rdg+20 digits)
AC Current	400A	\pm (3.0% of rdg+10 digits)
	1000A 0~800	\pm (3.5% of rdg+10 digits)
	800~1000	\pm (6.5% of rdg+10 digits)
Resistance	400 Ω	\pm (1.0% of rdg+3 digits)
	4k Ω /40k Ω /400k Ω /4M Ω	\pm (1.0% of rdg+2 digits)
	40M Ω	\pm (1.5% of rdg+3 digits)
Capacitance	51.2nF	\pm (3.0% of rdg+10 digits)
	512nF/5.12 μ F/51.2 μ F	\pm (2.5% of rdg+5 digits)
	100 μ F	\pm (5.0% of rdg+10 digits)
Temperature	-20~150°C	\pm (3°C+1 digit)
	150~1000°C	\pm (3% of rdg+2 digits)
Frequency	5.12Hz/51.2Hz/512Hz/5.12kHz	\pm (0.1% of rdg+5 digits)
Duty Cycle	0.1%~99.9%	\pm (2.0% of rdg+2 digits)