


CUSTOMER	TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes	Yes



⑥ ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	1-3 @20°C	3.96 ohms ±10%
D.C. RESISTANCE	5-4 @20°C	1.79 ohms ±10%
D.C. RESISTANCE	7-9 @20°C	0.184 ohms ±10%
INDUCTANCE	1-3 10kHz, 100mVAC, Ls	1.88mH ±10%
SATURATION CURRENT	20% rolloff from initial	360mA
LEAKAGE INDUCTANCE	1-3 tie(4+5, 7+9), 100kHz, 100mVAC, Ls	22.7uH typ., 34.1uH max.
⑥ DIELECTRIC	3-7 tie(3+4), 4500VAC, 1 second	3600VAC, 1 minute
URNS RATIO	(3-1):(7-9)	5:1, ±1%
URNS RATIO	(3-1):(5-4)	3.75:1, ±1%

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Designed to comply with the following requirements as defined by IEC60950-1, EN60950-1, UL60950-1/CSA60950-1 and AS/NZS60950.1:

- Reinforced insulation for a primary circuit at a working voltage of 400VDC.

Wire insulation & RoHS status not affected by wire color.
Wire insulation color may vary depending on availability.

DETAILS SUBJECT TO CHANGE

REV.	DATE	Packaging Specifications	Tolerances unless otherwise specified:	DRAWING TITLE	PART NO.
		Method: Tray KG-0995	Angles: ±1° Fractions: ±1/64	TRANSFORMER	FKS7508110333
			Decimals: ±.005 Footprint: ±.001		
			Dimensions		