



- Authentic nature wood patterns
- Excellent wear resistant
- Easy maintenance
- Stain, slip and scratch resistance
- Excellent dimensional stability
- Recommend for: residential and commercial decoration.

Specification			
Thickness	2.0~5.0mm		
Wear Layer	0.1~0.7mm		
Size Available	4inx36in / 6inx36in / 4inx24in / 7.25inx48in / 9inx48in (1in=25.4mm)		
Item	Standard	Unit	Result
Finish			UV
Abrasion	EN 660-2	mm ³	<2.0 Group T
Dimensional stability	EN 434 ASTM F2199	%	≤0.15%
Curling	EN 434	mm	≤2
Peel strength	EN 431	N/50mm	Residential >38 Commercial >45
Flexibility	EN435		No Crack
Castor chair suitable	EN 425		suitable
Color fasten to light	ISO105-B02	-	≥6
Color fasten to heat	ASTM F1514	-	No change
Stain resistance	EN 423	Class	0
Residual Indentation	EN433	-	≤0.1mm
Fire Behavior	EN ISO 9239-1		B _{FL} S ₁
VOC	CA Section 01350		Pass



BTL INDUSTRIES



BW-1001



BW-1002



BW-1005



BW-1006



BW-1007



BW-1010



BW-1013



BW-1016

BTL flooring

Focus on

LVT.Vinyl Roll.WPC Decking.Sport Flooring

www.btlfloor.com



BTL INDUSTRIES



BW-1017



BW-1020

The above pictures are just for references, please ask for samples before making final decision.
Please go to www.btlfloor.com or contact info@btlfloor.com for more information and colors.

BTL flooring

Focus on

LVT.Vinyl Roll.WPC Decking.Sport Flooring

www.btlfloor.com