

PRODUCT SPECIFICATION

浩然显示

PRODUCT : 3.2" TFTMODEL NO. : HT032CQV37TVERSION: V1.0DATE : 2011/12/06

CUSTOMER: _____

SPECIFICATION

FOR

HT032CQV37T

V 1.0

Customer Confirmation column

Approved by: _____ Dept.: _____ Data: _____

Please return one of the copies of the specifications with your signature to us within two weeks after you receive this document. If it is not returned, we will assume that you agree to the entire contents of this specification document.

HaoRan Display Confirmation column

Design: _____ Check: _____ Approval: _____

Shenzhen HaoRan Display Co., Ltd

PRODUCT SPECIFICATION

CONTENTS

No.	ITEM	PAGE
---	COVER	1
---	CONTENTS	2
---	RECORD OF REVISIONS	3
1.0	COMPOSITION	4
2.0	MECHANICAL SPECIFICATIONS	4
3.0	ELECTRICAL SPECIFICATIONS	5
4.0	DIMENSIONAL DIAGRAM	6
5.0	TERMINAL FUNCTIONS	7
6.0	BLOCK DIAGRAM	8
7.0	OPTICAL CHARACTERISTICS	9
8.0	RELIABILITY	13
9.0	STANDARDS OF INSPECTION ITEMS	14
10.0	PRECAUTIONS	15
11.0	FINAL REMARKS	16

PRODUCT SPECIFICATION

RECORDE OF REVISIONS

VERSION NO.	REVISION DETA	PAGE	DESCRIPTION
1.0	2011/12/06	16	NEW RELEASED

PRODUCT SPECIFICATION

1.0 COMPOSITION

Display type: [240(RGB) × 320 Dots, TFT LCD Module]

View Direction: [12 O'clock]

Backlight: [LED B/L White]

Driver IC: [ILI9341]

Operating temperature: [-20~+70°C]

Storage temperature: [-30~+80°C]

2.0 MECHANICAL SPECIFICATIONS

ITEM	STANDARD VALUES	UNITS
LCD type	3.2" TFT	
Pixel arrangement	240(RGB)×320	pixels
Module size	55.04×77.7×4.43	mm
Active area	48.6×64.8	mm
Pixel Pitch	202.5×202.5	um
Viewing direction	12 O'clock	

PRODUCT SPECIFICATION

3.0 ELECTRICAL SPECIFICATIONS**3.1 TFT-LCD Module Characteristics**

ITEM	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Power-supply Voltage	VDD	Ta = 25 °C	2.3	2.8	3.3	V
DC/DC Super Voltage	VCI	Ta = 25 °C	2.3	2.8	3.3	
Input Voltage	VIH	H level	$0.8 \times VDD$	—	VDD	
	VIL	L level	VSS	—	$0.2 \times VDD$	
Supply Current For Logic	IDD	VDD= 2.8V	—	3	—	mA
LCD Frame Frequency	FLM		—	60	—	Hz

3.2 Backlight Characteristics

ITEM	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Forward voltage	VF	IF=60mA	—	3.2	—	V
Uniformity	AVG		80	85	—	%
Luminance	Lv		4200	4500	—	Cd/m2

4.0 DIMENSIONAL DIAGRAM




PRODUCT SPECIFICATION

5.0 TERMINAL FUNCTIONS

Pin	Definition	Description
1~4	DB8~DB11	Data bus
5	GND	Ground
6	VCC	Power (2.8V)
7	CS	Chip selction signal
8	RS	Register selection signal
9	WR	Write signal
10	RD	Read signal
11	YU	Touch panel
12	XR	Touch panel
13	YD	Touch panel
14	XL	Touch panel
15	LEDA	LED Anode
16~21	LEDK1~LEDK6	LED Kathode
22	DB12	Data bus
23~30	DB0~DB7	Data bus
31	RESET	Hardware Reset
32	VCC	Power(2.8V)
33	IOVCC	Power (1.8~2.8V)
34	GND	Ground
35~37	DB13~DB15	Data bus

PRODUCT SPECIFICATION

6.0 BLOCK DIAGRAM



PRODUCT SPECIFICATION

7.0 OPTICAL CHARACTERISTICS

7.1 Measurement Parameter

ITEM		SYMBOL		CONDITIONS	MIN	TYP	MAX	UNITS
Viewing Angle		Hor	θL	C/R ≥ 10 B/L On	-	45	-	Deg
		·	θR		-	45	-	
		Her	φH		-	50	-	
		·	φL		-	20	-	
Luminance Of White(Center Point)		Y _L		φ = 0 θ = 0° Normal Viewing Angle B/L On	-	180	-	cd/m ²
Contrast Ratio		C/R			150	250	-	-
Response Time	Rising: T _R	T _R + T _F			-	30	50	ms
	Falling: T _F							
Color Chromaticity	White	x	φ = 0 θ = 0° Normal Viewing Angle B/L On		0.278	0.308	0.338	—
		y			0.316	0.346	0.376	
	Red	x			0.603	0.633	0.663	
		y			0.299	0.329	0.359	
	Green	x			0.264	0.294	0.324	
		y			0.546	0.576	0.606	
	Blue	x			0.103	0.133	0.163	
		y			0.092	0.122	0.152	

PRODUCT SPECIFICATION

7.2 Measurement System

Notes:

1. Definition of Contrast Ratio (CR):

The contrast ratio can be calculated by the following expression.

$$\text{Contrast Ratio (CR)} = L_{63} / L_0$$

L63: Luminance of gray level 63

L 0: Luminance of gray level 0

$$CR = CR(10)$$

CR (X) is corresponding to the Contrast Ratio of the point X at Figure 4

2. Surface luminance is the center point across the LCD surface 500mm from the surface with all pixels displaying white. For more information see FIG 1.
3. Response time is the time required for the display to transition from white to black (Rising Time, Tr) and from black to white (Falling Time, Tf). For additional information see FIG 2.
4. Viewing angle is the angle at which the contrast ratio is greater than 10. The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface. For more information see FIG 3.

FIG. 1 Measurement Set-Up:

The LCD module should be stabilized at a given temperature for 20 minutes to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting Backlight for 20 minutes in a windless room.

PRODUCT SPECIFICATION




FIG. 2 The definition of Response Time




FIG. 3 The definition of Viewing Angle

Use Fig. 1(Test Procedure) under Measurement System to measure the contrast from the measuring direction specified by the conditions as the following figure.

PRODUCT SPECIFICATION





FIG.4



PRODUCT SPECIFICATION

8.0 RELIABILITY

ITEM	CONDITIONS	CRITERIA
High temperature operation	70°C±2°C for 120 hours	◆ No defect in cosmetic and operational functions. ◆ Total current consumption below double of initial value.
Low temperature operation	-20 °C±2°C for 120 hours	
High humidity storage	50 °C±5°C, 90 % RH for 120 hours	
High temperature storage	80 °C±2°C for 200 hours	
Low temperature storage	-30 °C±2°C for 200 hours	
Temperature cycling	-20 °C±2°C (30 min) ↓↑ 25 °C±2°C (5 min) ↓↑ 70 °C±2°C (30 min) Cycles: 10	
Vibration	Frequency: 10Hz ~55Hz~10Hz Amplitude: 1.5mm Each Direction (X, Y, Z): 3hours (Packing condition)	
Hitting durability	250,000 times min. (Tip R12.5) 250g, 60 次/1min	
Pen sliding durability	100,000 times min. (Tip R0.8mm) 250g, 60mm/s	



Note:

- 1) The test samples should be applied to only one test item.
- 2) Sample size for each test item is 5~10pcs.
- 3) For Damp Proof Test, pure water(Resistance>1MΩ) should be used.
- 4) In case of malfunction defect caused by ESD damage, if it would be recovered to normal state after resetting, it would be judged as a good part.
- 5) EL evaluation should be excepted from reliability test with humidity and temperature: Some defects such as black spot/blemish can happen by natural chemical reaction with humidity and fluorescence EL has.
- 6) After the reliability test, the test samples should be inspected after 2 hours at least.
- 7) Functional test is OK. Missing segment, shorts, unclear segment, non display, display abnormally, liquid crystal leak are not allowed.
- 8) After testing, the current Idd should be within initial value ±20%.

No low temperature bubbles ,end seal loose and fall, frame rainbow, ACF bubble growing are allowable in the appearance test.

PRODUCT SPECIFICATION

9.0 STANDARDS OF INSPECTION ITEMS

NO	Item	Criterion	Level																						
01	Product condition	1.1 The part number is inconsistent with work order of product	Major																						
		1.2 Mixed product types	Major																						
		1.3 assembled in inverse direction	Major																						
02	quantity	The quantity is inconsistent with work order of product	Major																						
03	Outline dimension	product dimension and structure must conform to structure diagram	Major																						
04	electrical test	4.1 Missing line character and icon.	Major																						
		4.2 No function or no display	Major																						
		4.3 Display malfunction	Major																						
		4.4 LCD viewing angle defect.	Major																						
05	Black or white dot、scratch、contamination Round type $\Phi=(X+Y)/2$ 	Round type: <table><tr><th rowspan="2">Dimension (diameter : Φ)</th><th colspan="2">Acceptance (Q'ty)</th></tr><tr><th>A area</th><th>B area</th></tr><tr><td>$\Phi \leq 0.15\text{mm}$</td><td>Don't count</td><td>Don't count</td></tr><tr><td>$0.15\text{mm} < \Phi \leq 0.20\text{mm}$</td><td>2</td><td>Don't count</td></tr><tr><td>$\Phi > 0.25\text{mm}$</td><td>0</td><td>Don't count</td></tr></table>	Dimension (diameter : Φ)	Acceptance (Q'ty)		A area	B area	$\Phi \leq 0.15\text{mm}$	Don't count	Don't count	$0.15\text{mm} < \Phi \leq 0.20\text{mm}$	2	Don't count	$\Phi > 0.25\text{mm}$	0	Don't count	Minor								
Dimension (diameter : Φ)	Acceptance (Q'ty)																								
	A area	B area																							
$\Phi \leq 0.15\text{mm}$	Don't count	Don't count																							
$0.15\text{mm} < \Phi \leq 0.20\text{mm}$	2	Don't count																							
$\Phi > 0.25\text{mm}$	0	Don't count																							
06	Line type 	Line type: <table><tr><th rowspan="2">Length</th><th rowspan="2">Width</th><th colspan="2">Acceptance (Q'ty)</th></tr><tr><th>A area</th><th>B area</th></tr><tr><td>---</td><td>$W \leq 0.03\text{mm}$</td><td>Don't count</td><td>Don't count</td></tr><tr><td>$L \leq 2.5\text{mm}$</td><td>$0.03\text{mm} < W \leq 0.05\text{mm}$</td><td>2</td><td>Don't count</td></tr><tr><td>$L \leq 3.0\text{mm}$</td><td>$0.03\text{mm} < W \leq 0.05\text{mm}$</td><td>1</td><td>Don't count</td></tr><tr><td>---</td><td>$W > 0.05\text{mm}$</td><td colspan="2">As round type</td></tr></table>	Length	Width	Acceptance (Q'ty)		A area	B area	---	$W \leq 0.03\text{mm}$	Don't count	Don't count	$L \leq 2.5\text{mm}$	$0.03\text{mm} < W \leq 0.05\text{mm}$	2	Don't count	$L \leq 3.0\text{mm}$	$0.03\text{mm} < W \leq 0.05\text{mm}$	1	Don't count	---	$W > 0.05\text{mm}$	As round type		Minor
Length	Width	Acceptance (Q'ty)																							
		A area	B area																						
---	$W \leq 0.03\text{mm}$	Don't count	Don't count																						
$L \leq 2.5\text{mm}$	$0.03\text{mm} < W \leq 0.05\text{mm}$	2	Don't count																						
$L \leq 3.0\text{mm}$	$0.03\text{mm} < W \leq 0.05\text{mm}$	1	Don't count																						
---	$W > 0.05\text{mm}$	As round type																							
07	Touch Panel	7.1 No function.	Major																						
		7.2 The circuitry type must match type in specification sheet.	Major																						
		7.3 Appearance inspection as the glass.	Major																						
08	Backlight elements	8.1 Light leaks to induce deficiency lightness .	Major																						
		8.2 Backlight doesn't light or color is wrong.	Major																						
		8.3 Illumination source flickers when lit.	Major																						
		8.4 he contamination of backlight as NO.05.	Minor																						
09	Flexible Printed Circuit	9.1 FPC PIN type is inconsistent with specification sheet.	Major																						
		9.2 Short circuits in components on FPC.	Major																						
		9.3 A part of circuits in components on FPC is missing or wrong	Major																						
		9.4 The crack is in circuits of FPC.	Major																						

PRODUCT SPECIFICATION

10.0 PRECAUTIONS

10.1 Static charge

Since this LCD module contains CMOS LSIs that are sensitive to static charge, care must be taken when handling it.

10.2 Power on sequence

1. Input signals should not be applied to the LCD module before the logic system voltage has reached the specified voltage. If the above sequence is not kept the LCD module might be permanently damaged.
2. When connecting the power supply, connect the LCD bias voltage *after* connecting the logic system voltage.
3. When disconnecting the power supply, disconnect the logic system voltage *after* the LCD bias voltage.
4. It is recommended to connect a serial resistor or fuse to the LCD bias power supply of the system, as a current limiter. The value of the resistor depends on the kind of LCD used, but is typically 50 ~ 100 Ω .

10.3 Operation

1. It is essential to drive the LCD within the specified voltage limits, since a higher driving voltage than allowed causes a shorter LCD lifetime. Under these circumstances, electrochemical reactions will result in undesirable deterioration of the LCD.
2. The response time of the LC fluid is considerably longer at low temperatures than in the normal operating temperature range. On the other hand, the LCD will show a dark blue color at high temperatures. Those phenomena do not indicate a malfunction or defect of the LCD. Back at normal temperatures, the LCD will return to its original behavior.
3. If the display area is pressed hard during operation, some abnormal display patterns might appear. However, the display will resume normal operation after turning the module off and on.
4. Moisture on the terminals could cause an electrochemical reaction resulting in an open terminal connection. If the environmental temperature is higher than 40°C, it is required that the relative humidity is 50% or less.

10.4 Packaging

1. Do not leave the product in a place of high humidity for a long period. For storage in a location where the temperature is 35°C or higher, special care to protect the product from high humidity is required. A combination of high temperature and high humidity may cause polarization degradation and damage as well. Please keep the temperature and humidity within the specified range for storing.
2. Since LCD panels tend to be easily damaged, they should be handled with full care. Avoid any contact with materials that have a hardness of more than 2H.
3. Adhesives used for adhering upper/lower polarizers and aluminum plates are made of organic substances that will deteriorate by chemical reactions with for example chemicals such as acetone, toluene, ethanol, and isopropylalcohol. Please prevent the use of these chemicals and contact us when it is necessary for you to use other chemicals.
4. Immediately wipe off saliva or water drops from the display area with an absorbent cotton cloth, without scrubbing it. If adhered for a long period, such particles might cause deformation or faded color.
5. Moisture deposited on the display surface and contact terminals due to low temperatures will be a cause for polarizer damage, stains, and dirt. Before use, such panels should be slowly warmed up to a temperature that is higher than

PRODUCT SPECIFICATION

room temperature.

6. Touching the display area and contact terminals with bare hands is harmful to polarizer and may lead to poor insulation at the terminals.
7. The glass is fragile and can be cracked or chipped easily by handling, in particular on near its edge. Please prevent sudden shocks or exposing the glass to other sorts of stress.

10.5 Long-term storage

For long-term storage the following methods are highly recommended:

1. Store the product in a polyethylene bag with a sealed opening to prevent fresh air entering from the outside. Placing it with a desiccant is not necessary.
2. Store the product in a dark place, with the temperature in the range from 0 °C to 35 °C.
3. Keep the sensitive polarizer surface of the LCD panels clear of any contact. We recommend using the container that was used by SPACE DISPLAY to deliver the products.

10.6 Cleaning of the product

To clean the product make sure to use absorbent cotton cloth or other soft material like chamois. Make sure to rub it gently, and do not use chemicals when cleaning.

11.0 FINAL REMARKS

1. The above specifications are the binding criteria for ZhongLi DISPLAY Technology's outgoing quality inspection.
2. The customer is kindly requested to inform ZhongLi DISPLAY Technology as soon as possible on any questions, remarks, and disagreements regarding these specifications.
3. ZhongLi DISPLAY is not responsible for damage to its products due to neglect of the precautions as described in the previous chapter.