



Reputation Electronic Technology (HK) Co., Ltd
Shenzhen World Reputation Electronic Technology Co., Ltd

Add:6F,B Building,B Area, Xingqiang Business Building, NO.1,Dezheng Road, Shilong Community, Shiyan, Bao'an District,Shenzhen China

Skype: crystal.reputation

Mobile: +86 15920036963

Web: Http://www.yumite.hk

Mould Number	MN200	Mini laser barcode scanner platform
Technical parameter		
Light Source Type	Visual lasing diode;the wave length is 650mm.	
Trigger Mode	Manul and automatic optional	
Scanning Mode	Single-line scanning	
Scanning Speed	100±2 times/s	
Scan Precision	≥4mil	
Printing Contrast Ratio	The lowest reflectivity differece is 30%.	
Bit Error Rate	1/50million	
Environment Luminance	3000-12000 Lux	
Depth of field	5mm-630mm	
Scanning Angle	±60°±65°±42° (Left and right, front and back, rotation)	
Decoding capacity	UPC/EAN/JAN, UPC/EAN with Supplemental, UCC/EAN 128, Code 39, MSI,	
	Code11, Code 39 Full ASCII, Code 39 TriOptic, Code 128, Code 128Full ASCII,	
	Codabar, Code93, Discrete2of5, IATA, RSSvariants, Codabar, Chinese2of5,	
	International general dimensional barcodes, e.g. Intelveaved2/5, Interleaved2of5 and China postal	
Electical parameter		
Input voltage	5VDC±0.25V	
Power	250mW(work): 325mW(momentary maximum)	
Current	65mA(work): 135mA(momentary maximum)	
Standby Current	<100mA	
Prompt Mode	Buzzer and LED indicator	
Physical parameter		
Transfer cable interface	USB(standard):PS/2 and RS232 are selectable	
Dimension	L*W*H: 70mm*50mm*22mm	
Weight	58g(excluding cables)	
Cable standard	Straight line,1.8m	
Interface type	RJ-45 crystal head	
Outside material	ABS+PC	
Environment parameter		
Temperature	0°C to 50°C(work) : -40°C to 60°C(storage)	
Anti-knock capacity	This product can still work properly after falling from the height of 3m	



