

Order Codes	Capacity	W*D*H(mm)
T-WMB02 6404	4	600*450*220
T-WMB02 6406	6	600*450*358
T-WMB02 6409	9	600*450*492
T-WMB02 6612	12	600*450*625
T-WMB02 6415	15	600*450*730
T-WMB02 6418	18	600*450*820
T-WMB02 6422	22	600*450*960
T-WMB02 6427	27	600*450*1280

Brand:	TUXIN	Column spacing:	465mm (19 inch)
No:	T-WMB02 6406	Material:	SPCC cold rolled steel
Size:	600mm*450mm*6U	Function:	Can install server equipment、 the router 、 patch panel、 KVM、 UPS、 Network device etc.
IOS test:	Pass ISO9001:2008 Quality System	Thickness:	Mounting Profile: 1.5mm,others: 1.2/1.0mm
Surface treatment:	Degreasing,pickling,phosphating,power coating,etc.	Configuration:	Cage nuts and M6 screws: 10 sets.
Standard:	Comply with ANSI/EIA RS-310-D、 IEC297-2、 DIN41491; PARTI、 DIN41494; PART7、 GB/T3047.2-92 standard; compatible with ETSI	Device Installation:	It is recommended to install network equipment/server device within 350 mm depth.