

SHENZHEN BRILLIANT CRYSTAL TECHNOLOGIC CO.,LTD.

深圳市彩晶科技有限公司

The specification for the following models:

CM12232-5SLDAA-5

PROPOSED BY		APPROVED
Design	Approved	

TEL:+86-755-29995238

FAX:+86-755-29459900

[Http://www.cj86.com](http://www.cj86.com)

E-mail:13502819234@139.com


[Http://www.szcm-lcd.com](http://www.szcm-lcd.com)

E-mail:szcj86@hotmail.com

1. Mechanical Specification

ITEM	STANDARD VALUE			UNIT
Dot Matrix	122 X 32 DOTS			--
MODULE DIMENSION	76.5 (W) X 29 (H) X 7.5 (T)			mm
VIEWING DISPLAY AREA	60.5 (W) X 20.5 (H)			mm
ACTIVE DISPLAY AREA	48.75 (W) X 14.35 (H)			mm
DOT SIZE	0.36 (W) X 0.41 (H)			mm
DOT PITCH	0.04 (W) X 0.04 (H)			mm
DRIVE METHOD	1/32 Duty , 1/6 BIAS			
VIEWING DIRECTION	6 O'clock			
LCD type	STN yellowgreen			
Display mode	positive			
LED Backlight Color	Yellow Green			
Backlight Input	DC +5.0V			V
LED backlight current	30			mA
Backlight Half-Lift Time	35,000			HR.
INPUT VOLTAGE	DC +5.0V	V	1	mA
LCD DRIVER	1520			
Weight	22g			

2. Mechanical Diagram



3.Interface Pin Connections

NO	SYMBOL	LEVEL	FUNCTION
1	VDD	5V	Power Supply
2	VSS	0V	Power Ground
3	VLCD	0~+5V	LCD Drive Voltage
4	/RES	H/L	Reset Signal(enable at low)
5	E1	H/L	Enable signal of first IC
6	E2	H/L	Enable signal of second IC
7	R/W	H/L	Selection of READ or WRITE
8	A0	H/L	D/I="H", mean DB7~DB0 is Data D/I="L", mean DB7~DB0 is command
9	DB0	H/L	DATA BUS
10	DB1	H/L	DATA BUS
11	DB2	H/L	DATA BUS
12	DB3	H/L	DATA BUS
13	DB4	H/L	DATA BUS
14	DB5	H/L	DATA BUS
15	DB6	H/L	DATA BUS
16	DB7	H/L	DATA BUS
17	LEDK	--	LED(0V)
18	LEDA	--	LED(+5V)

4. Absolute Maximum Ratings

ITEM	SYMBOL	MIN.	TYPE	MAX.	UNIT
OPERATING TEMPERATURE	TOP	0/-20	--	+50/+70	℃
STORAGE TEMPERATURE	TST	-10/-30	--	+60/+80	℃
INPUT VOLTAGE	VI	4.75	5.0	5.25	V
SUPPLY VOLTAGE FOR LOGIC	VDD-VSS	--	5.0	5.5	V
SUPPLY VOLTAGE FOR LCD	VDD-VO	--	--	5.0	V
STATIC ELECTRICITY	Be sure that you are grounded when handing LCM.				