

### Technical Parameters

Model	Max. Feeding Size (mm)	Outlet adjusting Size(mm)	Capacity (t/h)	Motor Power (kw)	Weight (t)	Overall Dimension (mm)
PE150*250	125	10-40	1-3	5.5	0.7	1000*870*990
PE200X300	200×300	180	15-50	5.5	1.5	910*750*990
PE200X350	200×350	180	18-70	7.5	2.1	1000*870*990
PE250*400	210	20-60	5-20	15	2.8	1300*1090*1270
PE400*600	340	40-100	16-60	30	7	1730*1730*1630
PE400*900	340	40-100	40-110	55	7.5	1905*2030*1658
PE500×750	425	50-100	40-110	55	12	1980*2080*1870
PE600*900	500	65-160	50-180	75	17	2190*2206*2300
PE750*1060	630	80-140	110-320	90	31	2660*2430*2800
PE900*1200	750	95-165	220-450	160	52	3380*2870*3330
PE1000*1200	850	195-265	315-500	160	55	3480*2876*3330
PEX150*750	120	18-48	8-25	15	3.8	1200*1530*1060
PEX250*750	210	15-60	13-35	30	6.5	1380*1750*1540
PEX250*1000	210	15-60	16-52	37	7	1560*1950*1390
PEX250*1200	210	15-60	20-61	45	9.7	2140*2096*1500