

CSN-A2/A2L

2" MICRO PANEL PRINTER SERIES

- Smart appearance
- Easy paper loading
- Low noise thermal printing
- Different interfaces optional
- Front panel make paper replacement easily
- Easily embedded to any kinds of instruments and meters

MODEL		CSN-A2/CSN-A2L
Print	Printing Method	Thermal Line
	Printing Speed	90mm/s(max)
	Resolution	203dpi(8dots/mm)
	Effective Printing Width	48mm
Character	Character Set	ASCII,GB2312-80(Chinese)
	Print Font	ANK:9×17,12×24,GBK:24×24
Paper spec.	Paper Type	Thermal Paper
	Paper Width	57.5±0.5mm
	Paper Thickness	55-90 μm
	Paper Roll Diameter	Max:38mm
Reliability	TPH	50km(12.5% print ratio)
Interface		RS232/TTL/USB/Parallel
Power Supply (Adapter)		DC5V-9V/12V
Physical	Outline Dimension (WxLxH)	111×65×56.5mm
	Installation Port Size(WxL)	103.3×57.3mm
	Insert Depth	50mm
	Color	Black/Beige/Orange
Environment	Operating Temp	0° C~50° C
	Operating Humidity	10%~80%
	Storage Temp	-20° C~60° C
	Storage Humidity	10%~90%

