




深圳市星光彩科技有限公司
Shenzhen Xing Guang Cai Technology Co.,Limited

Outdoor P3.91 Full Color LED Display Parameter

LED Module		
	pixel pitch	3.91mm
	module size	250*250mm
	module resolution	64*64
	LED	SMD1921
	Scan	1/16 scan
	Application	outdoor

LED Cabinet		
	Cabinet Size	500mm (W) *500mm (H) / 500mm (W) *1000mm (H)
	Cabinet resolution	128*128dots / 128*256dots
	module quantity	2*2pcs / 2*4pcs
	Power supply	5V 60A 220V
	Material	Die casting aluminum
	Receiving card	1pcs

LED Screen				
	Pixel	65536dots/m ²	Continuous Working Hours	>72 hours
	Ave power consumption	500W/m ²	Using Life	100,000 hours
	Max power consumption	1200W/m ²	MTBF	>10,000H
	Optimum Viewing Distance(m)	≥4m	Scatter OOC Point	<0.01%
	Brightness(cd/m ²)	≥4000cd	Continuous OOC Point	None
	Refresh Rate	1920HZ	IP Grade	IP65/IP54
	LED Drive mode	Constant Current	Working Temperature	-35C----+60C
	Display color	17M——69G	Working Humidity	10---90%