

UL3266

Low Halogen Crosslinked Wire 低卤交联线

产品说明

- 额定温度:125℃
- 额定电压:300V
- 参考标准:UL758,UL1581,CSA C22.2No.210.2
- 导体使用单支或绞合镀锡或裸铜32 -10AWG
- XLPE 绝缘,符合ROHS 环保标准
- 通过UL VW-1、CSA FT1 阻燃测试
- 绝缘厚度均匀、易裁线、易剥皮
- 用于一般电子、电器设备内部连接线

PRODUCT DESCRIPTION

- Rated temperature: 125℃
- Rated voltage: 300V
- Reference standard: UL758,UL1581,CSA C22.2No.210.2
- Solid or stranded ,tinned or bare copper conductor32 -10AWG
- XLPE insulation ,comply with ROHS environmental standard
- Passes UL VW-1,CSA FT1 flame test
- Uniform insulation thickness to ensure easy stripping and cutting
- For general purpose internal wiring of appliance



印字 MARKING

AWM 3266 E330484 VW-1 125℃ 300V XXAWG B&T CABLE c AWM I A FT1 125℃ 300V XXAWG

产品结构 CABLE CONSTRUCTION

编号	导体 CONDUCTOR			绝缘 INSULATION	完成外径Overall diameter(mm)		最大导体电阻 MAX. COND. RESIS TANCE Ω /km, (20℃, DC)	参考 重量 Approx. weight (g/m)	参考 包装 Standard packing (m)
	规格 SIZE	构造 CONSTRUCTIO N (No. /mm)	外径 DIA (mm)	厚度 THICKNESS (mm)	标准Standard	公差 Tolerance			
32663007XX	30	7/0.10	0.30	0.40	1.10	±0.1	381	1.75	610
326630070SXX	30	7/0.10 OS=1	0.30	0.40	1.10	±0.1		1.6	
32663001XX	30	1/0.254	0.254	0.40	1.05	±0.1			
32662807XX	28	7/0.127	0.38	0.40	1.20	±0.1	239	2.26	610
32662807XX	28	7/0.127 OS=1	0.38	0.40	1.20	±0.1		1.95	
32662801XX	28	1/0.32	0.32	0.40	1.10	±0.1			
32662607XX	26	7/0.16	0.48	0.40	1.30	±0.1	150	2.94	610
32662601XX	26	1/0.40	0.40	0.40	1.25	±0.1		2.68	
32662411XX	24	11/0.16	0.61	0.40	1.40	±0.1			
32662407XX	24	7/0.20	0.60	0.40	1.40	±0.1	94.2	3.85	610
326624070SXX	24	7/0.20 OS=1	0.60	0.40	1.40	±0.1		3.57	
32662401XX	24	1/0.51	0.51	0.40	1.35	±0.1			
32662217XX	22	17/0.16	0.76	0.40	1.60	±0.1	60.16	5.44	610
32662207XX	22	7/0.254	0.76	0.40	1.60	±0.1		4.95	
326622070SXX	22	7/0.254 OS=1	0.76	0.40	1.60	±0.1			
32662201XX	22	1/0.64	0.64	0.40	1.50	±0.1	38.58	7.58	610
32662026XX	20	26/0.16	0.94	0.40	1.80	±0.1		7	
32662010XX	20	10/0.254	0.94	0.40	1.80	±0.1			
32662007XX	20	7/0.32	0.94	0.40	1.80	±0.1	22.98	11.18	610
32662001XX	20	1/0.813	0.813	0.40	1.65	±0.1		11.07	
32661841XX	18	41/0.16	1.20	0.40	2.10	±0.1		10.1	
32661816XX	18	16/0.254	1.20	0.40	2.10	±0.1	15.06	16.45	610
32661801XX	18	1/1.024	1.024	0.40	1.85	±0.1		15.36	
32661626XX	16	26/0.254	1.50	0.40	2.40	±0.1			
32661601XX	16	1/1.29	1.29	0.40	2.20	±0.1			

