



Eanovo Technology (Shenzhen) Co., Ltd

A Building, ShangXue Technology Industrial Park, BanTian,LongGang , Shenzhen, Guangdong. China.

Contact person: Lena Lee

Mob/whatsapp: 86-15899766616

Tel:86-755-83721915 Fax:86-755-26062035

Email:lena@eanovo.com.cn

Skype:lena0621

http://www.eanovo.com.cn

http://www.globalsources.com/eanovo.co

Quotation

Unit Price (USD)	3kpcs	2000pcs	1000pcs	Sample	8 inch 3G 4G IP67 Rugged Tablet Specification		Model NO.: EA-M8R
          					CPU	Intel Cherrytrail Z8350, 1.44Ghz-1.92GHz	
					GPU	Intel® HD Graphics	
					RAM	2GB LPDDR3 (4G Optional)	
					ROM	EMMC 32GB (64G / 128G Optional)	
					Storage Extend	SD/TF Support , Max: 128G	
					LCD	8inch 16:10; 800*1280 IPS LCD; Brightness:320Nit	
					TP	Support handwriting; Multipoints Capacitive, G+G, Rigidity: above 7H-Anti-scratch,	
					OS	windows 10 Smode 32bit; Default language:English (Windows10 Pro 32bit/64bit Optional)	
					WiFi	WIFI 802.11(a/b/g/n/ac), frequency 2.4G+5.8G dual band WIFI, intel 3165D2WG	
					Bluetooth	BT4.2 (BLE) class 1 transmission distance:10m	
					3G	build in, WCDMA(900/2100MHz) GSM (900/1800MHz)	
					4G	build in (Optional), LTE FDD: B1/B3/B5/B7/B8/B20 LTE TDD: B38/B40/B41 WCDMA: B1/B5/B8 GSM: B3/B8	
					Camera	front 2.0MP with indicator light, Rear 5MP	
					Speaker	build in, Embedded 8Ω/0.8W waterproof speaker x 1	
					Mic	build in, Sensitivity:-42db, output resistance2.2kΩ	
					Battery	Type: build in polymer li-ion battery	
						Capacity: 3.7V / 8500mAh (If use 4G configuration, battery capacity is 7800MAH)	
						Endurance: 8Hrs(default 50% volumn, default200 lumens brightness, play 1080P HD video)	
					Power Adaptor	AC100V ~ 240V, 50Hz/60Hz output DC 5V/3A , CE approval	
					G-SENSOR	build in Gravity acceleration sensor	
					GPS	build in	
					FPI	support Optional	
					Iris recognition	support Optional	
					QR Code	support Optional	
					RFID	support Optional	
					NFC	build in	
					interface	1 x USB2.0(host), 1 x DC charging, 1 x TF Card Slot, 2 x SIM Card Slot, 1 x 3.5mm headphone jack, 1 x HDMI 1.4a Type C, 1 x 12pin Pogo Pin(Extensive Slot)	
					Product Certificate	IP67, CE NB, MIL-STD-810G, Battery(UN38.3, MSDS,IEC62133)	
					Product Reliability	Drop Height : 1.2m composite wood floors, in operation status	
						Operate Temperature : -10 °C to 50 °C	
						Store Temperature : -30 °C to 70 °C	
						Humidity: 95% Non-Condensing	
					Color	black+ silver (bottom shell in silver color, front shell in black) (Can be Customized)	
					Dimensions	228*145*16.5mm	
					Weight	Device unit: 750g, Unit with giftbox and standard accessories:1400g, docking:290g	
					Accessories	1 x Micro USB cable; 1 x OTG cable; 1 x Power Adaptor; 1 x User's Manual	

Term of price: EX work

MOQ:1000pcs per item for OEM

Payment: 30% T/T in advance, 70% T/T before shipment

Lead Time: Sample: 3~5 days, order: 20 days for 1000pcs

Warranty: 12 months