




## EASY-CAP WIRE CONNECTORS

### Features

- UL 486C Listed and tested to CSA 22.2 No. 188.
- Rated at 600 V Max. for building wiring and 1000 V Max. in lighting fixtures/luminaries and signs.
- Strong, durable, UL 94V-2 flame-retardant thermoplastic shell.
- Swept-back easy wings design provided firm and comfortable twisting.
- Inserted with fixed, square-wire spring which grabs wires quickly and firmly.
- Color coded to industry standards.
- Available in specific packing request and private labeling.



### Dimensions

| Model     | A    |       | B     |       | C     |       | D     |       | E     |       |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
|           | mm   | in.   | mm    | in.   | mm    | in.   | mm    | in.   | mm    | in.   |
| <b>N1</b> | 7.30 | 0.287 | 10.90 | 0.429 | 12.50 | 0.492 | 10.60 | 0.417 | 25.20 | 0.992 |
| <b>N2</b> | 9.10 | 0.358 | 13.20 | 0.520 | 14.80 | 0.583 | 11.50 | 0.453 | 29.50 | 1.161 |

### Ratings

| Model     | Color  | Elec. Rating & Wire Range                                                                      | Approval                                                                                 |                                                                                     | Packing                                   | Cat. No.     |
|-----------|--------|------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------|--------------|
| <b>N1</b> | Yellow | 600 V Max.<br>Temp. 105°C (221°F)<br>No. 22 - No. 10 AWG<br>Max. 3 #12<br>Min. 4 #22           | c  US |  | Box of 100                                | <b>N1000</b> |
|           |        |                                                                                                |                                                                                          |                                                                                     | Ctn of 5,000<br>(10 plastic bags, 500 ea) | <b>N1001</b> |
|           |        |                                                                                                |                                                                                          |                                                                                     | Bag of 25<br>(Bag packed with header)     | <b>N1002</b> |
| <b>N2</b> | Red    | 600 V Max.<br>Temp. 105°C (221°F)<br>No. 22 - No. 6 AWG<br>Max. 1 #8 w/3 #12 Str<br>Min. 3 #20 | c  US |  | Box of 100                                | <b>N2000</b> |
|           |        |                                                                                                |                                                                                          |                                                                                     | Ctn of 5,000<br>(10 plastic bags, 500 ea) | <b>N2001</b> |
|           |        |                                                                                                |                                                                                          |                                                                                     | Bag of 25<br>(Bag packed with header)     | <b>N2002</b> |