

SR26 Specification

SR26 开关规格说明书

项目 item		系列 series	SR26 系列 series
使用温度 Operating temperature			-21℃ to 70℃
储存温度 Storage temperature			-30℃ to 80℃
最大额定功率 Max.rated power			0.15A 250VAC/DC, 0.3A 110VAC/DC
电 性 能 electrical property	接触电阻 contact resistance		50mΩ max
	绝缘电阻 Insulation resistance		1000MΩ min. 500VDC
	耐电压 withstand voltage		500V AC for 1 min.
机械性能 Mechanical property	端子强度 terminal strength		5N for 1min
	旋转力矩 Rotating torque		0.03-0.08N.m
	止档强度 End Stop Strength		≥5kgf.cm
	焊接耐热性能 soldering and heat resisting property	手工焊接 H.W.	300 ± 5℃ 3s
		自动焊接 A.W.	260 ± 5℃ 4s
机械耐 久性能 Mechanical endurance	≥10000 次, 6-8 次/分钟 More than 10,000 cycles at a rate of 6-8 cycles per minute.		
包装说明 Package	纸箱尺寸 Carton Size		39 X 29 X 37cm
	泡沫箱尺寸 Foam		275 X 185 X 40mm
	包装数量 Quantity		50 只/盒, 20 盒/箱, 1000 只/箱 50pcs/box,20boxes/carton,1000pcs/carton
注意事项 Caution	本产品需密封保存 Sealed Storage		