

Audio product configuration table

Product Model			HV-R308			File Number	RD-GGS-032
						file version	V/0
draft	Liu Zhenkun	Review		Approval		Date	2026/5/22
							Page 1 of 1
	product image						
	Product Description	Portable Bluetooth karaoke sound system					
power configuration	power supply method	TYPE-C 5V					
	voltage range	DC 5V/2A					
	battery	7.4V/6600mA					
	Charging time	4H 36M					
	discharge time	3H38M					
	discharge time	9 hours and 30 minutes [50% volume discharge]					
Speaker configuration	Speaker specifications	5" woofer x1 + 2.5" full-range speaker x2					
Bluetooth solution	Bluetooth IC	JL7031					
	Bluetooth version	V5.3					
	Bluetooth range	Greater than 15 meters					
Power amplifier configuration	Power amplifier IC	AD52070X2					
Function Configuration	Display screen	☐ Yes ☒ No Note: Digital display					
	USB mode	☐ Supported formats: mp3/mp2/wav/wma/flac					
	AUX mode	☐ Being and Non-being					
	SD mode	☒ Supported formats:					
	TF mode	☒ Supported formats:					
	FM mode	☐ Frequency range: 87.5MHz~108MHz					
	call function	☒ Yes No					
	EQ function	☒ Yes No					
	TWS function	☒ With ☐ None Note: Two audio devices can be interconnected					
	MIC/Guitar	☒ With ☐ No					
	DC IN	☐ Yes ☒ No Note:					
	Light	Note: LED seven-color light with speaker (red, orange, yellow, green, blue, sky blue, purple)					
	Remote control function	☐ Yes ☒ No Note:					
	waterproof function	☒ Being and Non-being					
Parameter	Maximum output power	50W					

Configurat ion	Output power with THD=10%	30W+10WX2
	Standby power consumption	$\leq 0.5W$
	Maximum power consumption	60W
	frequency response range	50HZ-20KHZ
	S/N Signal-to- Noise Ratio	$\geq 75DB$
Dimensio ns and Weight	Product Dimensions	L377*W197*H237MM
	color box dimensions	443*238*264mm
	outer box dimensions	491*458*553mm, 4 pieces/box
	Net value (KG)	18.2kgs
	Gross weight (KG)	21.8kgs