

What can we custom?

Item	Contents
Construction:	lcd,cog, lcd+bl, lcd+bl+cob, according to your requirements
LCD type:	VA(NBT/EBN/IBN), TN, HTN, STN, FSTN, FFSTN/DFSTN
Polarizer:	Transflective, Transmissive, Reflective, Anti-Glare, Anti-UV
Background:	Gray, Yellow-Green, Blue, Black, white
Viewing direction:	6:00, 12:00, 3:00, 9:00, Customization
Operating temperature:	0 °C to 50 °C, -20 °C to +70 °C, -30 °C to +80 °C, -30 °C to +85 °C, Customization
Storage temperature:	-10 °C to +60 °C, -20 °C to +70 °C, -30 °C to +80 °C, -40 °C to +90 °C, Customization
Drive Method	Static or dynamic
Voltage(VOP):	according to your requirement
Connection:	Metal PIN, Rubber/Zebra, Heat seal, Flat cable(FPC)
Pitch of Metal PIN:	1.27mm, 1.5mm, 1.8mm, 2.0mm, 2.54 mm
Thickness of Glass:	2.8mm, 2.2mm
Silkprint:	Without, with 1 to 4 colors
Backlight color	Rgb ,white,blue,yellow,yellow green and so on
Interface	SPI serial,i2c serial,three line serial,uart,usb and so on
Quality control:	Strictly tested one by one to make sure all the goods best quality Each item has been checked and in good condition before shipping
Warranty:	12 Months free,payed life time