




□刀片刺绳

■Razor Wire Mesh



外径 Outside diameter	圈数 No.of loops	标准覆 盖长度 Standard length per coil	生产形式 Type	备注 Notes
450mm	33	7-8m	CBT-60.65	Single coil
500mm	56	12-13m	CBT-60.65	Single coil
700mm	56	13-14m	CBT-60.65	Single coil
960mm	56	14-15m	CBT-60.65	Single coil
450mm	56	8-9m	BTO-12.22.25.30	Cross type
500mm	56	9-10m	BTO-12.22.25.30	Cross type
600mm	56	10-11m	BTO-12.22.25.30	Cross type
600mm	56	8-10m	BTO-12.22.25.30	Cross type
700mm	56	10-12m	BTO-12.22.25.30	Cross type
800mm	56	11-13m	BTO-12.22.25.30	Cross type
900mm	56	12-14m	BTO-12.22.25.30	Cross type
960mm	56	13-15m	BTO-12.22.25.30	Cross type
980mm	56	14-16m	BTO-12.22.25.30	Cross type

刀片规格 Reference number	刀片样式 Blade style	刀片厚度 Thickness(mm)	心线直径 Wire dia.(mm)	刀长 Barb length(mm)	刀宽 Barb width(mm)	刀间距 Barb spacing(mm)
BT0-12		0.5 ± 0.05	2.5 ± 0.1	12 ± 1	15 ± 1	26 ± 1
BT0-15		0.5 ± 0.05	2.5 ± 0.1	15 ± 1	15 ± 1	33 ± 1
BT0-22		0.5 ± 0.05	2.5 ± 0.1	22 ± 1	15 ± 1	34 ± 1
BT0-30		0.5 ± 0.05	2.5 ± 0.1	30	18	45 ± 1
CBT-60		0.6 ± 0.05	2.5 ± 0.1	60 ± 2	32 ± 1	100 ± 2
CBT-65		0.6 ± 0.05	2.5 ± 0.1	65 ± 2	21 ± 1	100 ± 2

