



CE EMC TEST REPORT

For

ShenZhen JMK Technology Co., Ltd

Product Name:	LED Strip
Trademark:	N/A
Model :	KS01-2835-72LED KS01-2835-60LED, KS01-3014-60LED, KS01-3014-120LED, KS01-3014-204LED, KS01-4014-70LED, KS01-4014-140LED, KS01-5630-60LED, KS01-3528-60LED, KS01-3528-120LED, KS01-4014-60LED, KS01-4014-120LED, KS01-5050RGB-30LED, KS01-5050RGB-60LED, KS01-5050RGB-30LED-IC2811, KS01-5050RGB-60LED-IC2811.
Prepared For :	ShenZhen JMK Technology Co., Ltd
Address:	301, Building 2, District 2, Fuhai Industrial Zone, Fuyong Street, Baoan Shenzhen, China.
Prepared By :	Shenzhen BCTC Technology Co., Ltd.
Address:	A.Floor 3, 44 Building, Tanglang Industrial Park B, Taoyuan Street, Nanshan District, Shenzhen, China
Test Date:	Feb.03 - Feb. 10, 2015
Date of Report :	Feb. 10, 2015
Report No.:	BCTC-150201601



TABLE OF CONTENTS

TEST REPORT DECLARATION	5
1. GENERAL INFORMATION	6
1.1. Report information	6
1.2. Measurement Uncertainty	6
2. PRODUCT DESCRIPTION	7
2.1. EUT Description	7
2.2. Block Diagram of Test Setup	7
2.3. Test Conditions	7
2.4. Modifications	7
2.5. Abbreviations	8
2.6. Performance Criterion	8
3. TEST EQUIPMENT USED	9
3.1. For Conducted Emission Test	9
3.2. For Magnetic Test (In Shielding Room)	9
3.3. For Harmonic / Flicker Test	9
3.4. For Electrostatic Discharge Immunity Test	9
3.5. For RF Strength Susceptibility Test	9
3.6. For Electrical Fast Transient/Burst Immunity Test	9
3.7. For Surge Test	9
3.8. For Injected Currents Susceptibility Test	10
3.9. For Magnetic Field Immunity Test	10
3.10. For Voltage Dips and Interruptions Test	10
3.11. For Radiated emission Test	10
4. POWER LINE CONDUCTED EMISSION TEST	11
4.1. Block Diagram of Test Setup	11
4.2. Test Standard	11
4.3. Power Line Conducted Emission Limit	11
4.4. EUT Configuration on Test	11
4.5. Operating Condition of EUT	12
4.6. Test Procedure	12
4.7. Test Result	12
5. MAGNETIC TEST	13
5.1. Block Diagram of Test Setup	13
5.2. Test Standard	13
5.3. Magnetic Field Emission Limits	13
5.4. EUT Configuration on Test	13
5.5. Operating Condition of EUT	13
5.6. Test Procedure	13
5.7. Test Results	14
6. HARMONIC CURRENT EMISSION TEST	16
6.1. Block Diagram of Test Setup	16
6.2. Test Standard	16
6.3. Operating Condition of EUT	16
6.4. Test Procedure	16
6.5. Test Results	16



7. VOLTAGE FLUCTUATIONS & FLICKER TEST	17
7.1. Block Diagram of Test Setup	17
7.2. Test Standard.....	17
7.3. Operating Condition of EUT.....	17
7.4. Test Results	17
8. ELECTROSTATIC DISCHARGE TEST	18
8.1. Block Diagram of ESD Test Setup	18
8.2. Test Standard.....	18
8.3. Severity Levels and Performance Criterion	18
8.4. EUT Configuration on Test.....	18
8.5. Operating Condition of EUT	18
8.6. Test Procedure.....	19
8.7. Test Results	19
9. RF FIELD STRENGTH SUSCEPTIBILITY TEST	21
9.1. R/S Test Setup.....	21
9.2. Test Standard.....	21
9.3. Severity Levels and Performance Criterion	21
9.4. EUT Configuration on Test.....	21
9.5. Operating Condition of EUT.....	22
9.6. Test Procedure.....	22
9.7. Test Results	22
10. ELECTRICAL FAST TRANSIENT/BURST IMMUNITY TEST	24
10.1 Block Diagram of EUT Test Setup	24
10.2 Test Standard	24
10.3 Severity Levels and Performance Criterion	24
10.4 EUT Configuration on Test.....	25
10.5 Operating Condition of EUT.....	25
10.6 Test Procedure	25
10.7 Test Results.....	25
11. SURGE TEST.....	26
11.1. Surge Test Setup	26
11.2. Test Standard.....	26
11.3. Severity Levels and Performance Criterion	26
11.4. EUT Configuration on Test.....	26
11.5. Operating Condition of EUT.....	26
11.6. Test Procedure.....	27
11.7. Test Results	27
12. INJECTED CURRENTS SUSCEPTIBILITY TEST.....	28
12.1 Block Diagram of EUT Test Setup	28
12.2 Test Standard	28
12.3 Severity Levels and Performance Criterion	28
12.4 EUT Configuration on Test.....	29
12.5 Operating Condition of EUT.....	29
12.6 Test Procedure	29
12.7 Test Result	30
13. MAGNETIC FIELD IMMUNITY TEST.....	31
13.1 Block Diagram of Test Setup.....	31
13.2 Test Standard	31
13.3 Severity Levels and Performance Criterion	31
13.4 EUT Configuration on Test.....	32
13.5 Operating Condition of EUT.....	32



13.6 Test Procedure	32
13.7 Test Results	32
14. VOLTAGE DIPS AND INTERRUPTIONS TEST	33
14.1 Voltage Dips and Interruptions Test Setup	33
14.2 Test Standard	33
14.3 Severity Levels and Performance Criterion	33
14.4 EUT Configuration on Test.....	33
14.5 Operating Condition of EUT.....	33
14.6 Test Procedure.....	34
14.7 Test Result.....	34
15. RADIATION EMISSION TEST	35
15.1 Block Diagram of Test Setup.....	35
15.2 Test Standard	35
15.3 Radiation Limit	36
15.4 EUT Configuration on Test.....	36
15.5 Operating Condition of EUT.....	36
15.6 Test Procedure	36
15.7 Test Result	36
16. APPENDIX I EUT PHOTO.....	39
17. APPENDIX II EUT TEST PHOTO	41

**TEST REPORT DECLARATION**

Applicant	:	ShenZhen JMK Technology Co., ltd
Address	:	301, Building 2, District 2, Fuhai Industrial Zone, Fuyong street, Baoan district, Shenzhen, China.
Manufacturer	:	ShenZhen JMK Technology Co., ltd
Address	:	301, Building 2, District 2, Fuhai Industrial Zone, Fuyong street, Baoan district, Shenzhen, China.
EUT Description	:	LED Strip
Model Number	:	KS01-2835-72LED
Rating(s)	:	DC24V===

Test Procedure Used:

EMI : EN 55015: 2013

EN 61000-3-2 :2014; EN 61000-3-3: 2013

EMS : EN 61547: 2009

EN 61000-4-2 :2009, EN 61000-4-3 :2006+A1:2008+A2:2010,

EN 61000-4-4 :2012, EN 61000-4-5 :2014,

EN 61000-4-6: 2014, EN 61000-4-8 :2010, EN 61000-4-11 :2004

The EUT described above is tested by BCTC Technology Co., Ltd. EMC Laboratory to determine the maximum emissions from the EUT and ensure the EUT to be compliance with the immunity requirements of the EUT. BCTC Technology Co., Ltd. EMC Laboratory is assumed full responsibility for the accuracy of the test results. Also, this report shows that the EUT technically complies with the 2014/30/EU directive and its amendment requirements.

The test report is valid for above tested sample only and shall not be reproduced in part without written approval of the laboratory.

Date of Test:

Feb.03 - Feb. 10, 2015

Prepared by(Engineer):

Snow Zeng

Reviewer(Quality Manager):

Sophie Lee

Approved & Authorized Signer(Manager):

Casey Wang





1. GENERAL INFORMATION

1.1. Report information

1.1.1. This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that BCTC approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that BCTC in any way guarantees the later performance of the product/equipment.

1.1.2. The sample/s mentioned in this report is/are supplied by Applicant, BCTC therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.

1.1.3. Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through BCTC, unless the applicant has authorized BCTC in writing to do so.

1.2. Measurement Uncertainty


Available upon request.

2. PRODUCT DESCRIPTION

2.1. EUT Description

Description	:	LED Strip
Applicant	:	ShenZhen JMK Technology Co., ltd 301, Building 2, District 2, Fuhai Industrial Zone, Fuyong street, Baoan district, Shenzhen, China.
Manufacturer	:	ShenZhen JMK Technology Co., ltd 301, Building 2, District 2, Fuhai Industrial Zone, Fuyong street, Baoan district, Shenzhen, China.
Model Number	:	KS01-2835-72LED

2.2. Block Diagram of Test Setup



Operating Condition of EUT

Test mode 1: Work model

2.3. Test Conditions

Temperature: 23-25°C

Relative Humidity: 55-68 %

2.4. Modifications

No modification was made.

2.5. Abbreviations

AC	Alternating Current
AMN	Artificial Mains Network
DC	Direct Current
EM	ElectroMagnetic
EMC	ElectroMagnetic Compatibility
EUT	Equipment Under Test
IF	Intermediate Frequency
RF	Radio Frequency
rms	root mean square
EMI	Electromagnetic Interference
EMS	Electromagnetic Susceptibility

2.6. Performance Criterion

Criterion A: The equipment shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer when the equipment is used as intended.

Criterion B: After the test, the equipment shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed, after the application of the phenomena below a performance level specified by the manufacturer, when the equipment is used as intended.

Criterion C: Loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls by the user in accordance with the manufacturer's instructions.



3. TEST EQUIPMENT USED

3.1. For Conducted Emission Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Test Receiver	Rohde & Schwarz	ESHS30	828985/018	Aug. 25, 14	1 Year
2	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	Aug. 25, 14	1 Year
3	L.I.S.N.	Rohde & Schwarz	ESH2-Z5	834549/005	Aug. 25, 14	1 Year
4	Conical	Emtek	N/A	N/A	N/A	N/A
5	Voltage Probe	Schwarzbeck	TK9416	N/A	Aug. 25, 14	1 Year
6	Coaxial Switch	Anritsu	MP59B	6100214550	Aug. 25, 14	1 Year

3.2. For Magnetic Test (In Shielding Room)

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Test Receiver	Rohde & Schwarz	ESHS30	828985/018	Aug. 25, 14	1 Year
2	Triple-loop Antenna	Rohde & Schwarz	HM020	843885/002	Aug. 25, 14	1 Year
3	RF Cable	MIYAZAKI	5D-2W	Tri-loop Cable	Aug. 25, 14	1 Year
4	Coaxial Switch	Anritsu	MP59B	M73989	Aug. 25, 14	1 Year

3.3. For Harmonic / Flicker Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Power Frequency test system	HAEFELY	PHF555	080419-03	Aug. 25, 14	1 Year

3.4. For Electrostatic Discharge Immunity Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	ESD Tester	HAEFELY	PSD 1600	H911'292	Aug. 25, 14	1 Year

3.5. For RF Strength Susceptibility Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Signal Generator	HP	8648A	3633A02081	Aug. 25, 14	1 Year
2	Amplifier	A&R	500A100	17034	N/A	N/A
3	Amplifier	A&R	100W/1000M1	17028	N/A	N/A
4	Isotropic Field Monitor	A&R	FM2000	16829	N/A	N/A
5	Isotropic Field Probe	A&R	FLW220100	16755	Aug. 25, 14	1 Year
6	Biconic Antenna	EMCO	3108	9507-2534	N/A	N/A
7	Log-periodic Antenna	A&R	AT1080	16812	N/A	N/A
8	PC	N/A	486DX2	N/A	N/A	N/A

3.6. For Electrical Fast Transient/Burst Immunity Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Burst Tester	HAEFELY	PEFT4010	080981-16	Aug. 25, 14	1 Year
2	Coupling Clamp	HAEFELY	IP-4A	147147	Aug. 25, 14	1 Year

3.7. For Surge Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Surge Tester	HAEFELY	PSURGE4.1	080107-04	Aug. 25, 14	1 Year



3.8. For Injected Currents Susceptibility Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Simulator	EMTEST	CWS 500C	0900-12	Aug. 25, 14	1 Year
2	CDN	EMTEST	CDN-M2	510010010010	Aug. 25, 14	1 Year
3	VDN	EMTEST	CDN-M3	0900-11	Aug. 25, 14	1 Year
4	Injection Clamp	EMTEST	F-2031-23MM	368	Aug. 25, 14	1 Year
5	Attenuator	EMTEST	ATT6	0010222a	Aug. 25, 14	1 Year

3.9. For Magnetic Field Immunity Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Magnetic Field Tester	HEAFELY	MAG100.1	083858-10	Aug. 25, 14	1 Year

3.10. For Voltage Dips and Interruptions Test


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Dips Tester	HEAFELY	PLINE 1610	083732-18	Aug. 25, 14	1 Year

3.11. For Radiated emission Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	ANRITSU	MS2661C	6200140915	Aug. 25, 14	1 Year
2.	Test Receiver	Rohde & Schwarz	ESHS30	828985/018	Aug. 25, 14	1 Year
3.	Bilog Antenna	Schwarzbeck	VULB9163	142	Aug. 25, 14	1 Year
4.	50 Coaxial Switch	Anritsu Corp	MP59B	6100237248	Aug. 25, 14	1 Year
5.	EMI Power Line Filter	DUOJI EME	FNF 201 B16	N/A	Aug. 25, 14	1 Year
6.	EMI Power Line Filter	JIANLI	DL-40C	N/A	Aug. 25, 14	1 Year
7.	Cable	Schwarzbeck	AK9513	ACRX1	Aug. 25, 14	1 Year
8.	Cable	Rosenberger	N/A	FP2RX2	Aug. 25, 14	1 Year
9.	Cable	Schwarzbeck	AK9513	CRPX1	Aug. 25, 14	1 Year
10.	Cable	Schwarzbeck	AK9513	CRRX2	Aug. 25, 14	1 Year
11.	Signal Generator	HP	8648A	3625U00573	Aug. 25, 14	1 Year

4. POWER LINE CONDUCTED EMISSION TEST

4.1. Block Diagram of Test Setup



4.2. Test Standard

EN 55015: 2013

4.3. Power Line Conducted Emission Limit

Frequency	At mains terminals (dBμV)	
	Quasi-peak Level	Average Level
9KHz ~ 50KHz	110	N/A
50KHz ~ 150KHz	90 ~ 80*	N/A
150KHz ~ 0.5MHz	66 ~ 56*	56 ~ 46*
0.5MHz ~ 2.51MHz	56	46
5.0MHz ~ 30MHz	60	50

1. At the transition frequency the lower limit applies.
2. * decreasing linearly with logarithm of the frequency.

4.4. EUT Configuration on Test

The following equipments are installed on conducted emission test to meet EN55015 requirement and operating in a manner, which tends to maximize its emission characteristics in a normal application.

4.4.1. LED Strip (EUT)

Model Number : **KS01-2835-72LED**

Manufacturer : **ShenZhen JMK Technology Co., ltd**



4.5. Operating Condition of EUT

- 4.5.1. Setup the EUT and simulators as shown in Section 4.1.
- 4.5.2. Turn on the power of all equipments.
- 4.5.3. Let the EUT work in test modes (EUT WORKING) and test it.

4.6. Test Procedure

The EUT is put on the table which is 0.8 meter high above the ground and connected to the AC mains through a Line Impedance Stabilization Network (L.I.S.N.). This provided a 50ohm coupling impedance for the tested equipments. Both sides of AC line are checked to find out the maximum conducted emission according to the **EN55015** regulations during conducted emission test. And the voltage probe had been used for the load terminals test according to the **EN55015** standard.

The bandwidth of the test receiver (R&S Test Receiver ESHS30) is set at 10KHz. In 150KHz~30MHz and 200Hz bandwidth in 9KHz~150KHz.


The frequency range from 9KHz to 30MHz is checked.

4.7. Test Result

N/A

5. MAGNETIC TEST

5.1. Block Diagram of Test Setup



(EUT: LED Strip)

5.2. Test Standard

EN 55015: 2013

5.3. Magnetic Field Emission Limits

Frequency	Limits for loop diameter (Db μ A)
	2m
9KHz ~ 70KHz	88
70KHz ~ 150KHz	88 ~ 58*
150KHz ~ 3.0MHz	58 ~ 22*
3.0MHz ~ 30MHz	22

1. At the transition frequency the lower limit applies.
2. * decreasing linearly with logarithm of the frequency.

5.4. EUT Configuration on Test

The configuration of the EUT is same as Section 3.2..

5.5. Operating Condition of EUT

5.5.1. Setup the EUT as shown in Section 5.1.

5.5.2. Turn on the power of all equipments.

5.5.3. Let the EUT work in test mode (ON) and test it.

5.6. Test Procedure

The EUT is placed on a wood table in the center of a loop antenna. The induced current in the loop antenna is measured by means of a current probe and the test receiver. Three field components is checked by means of a coax switch.

The frequency range from 9KHz to 30MHz is investigated. The receiver is measured with the quasi-peak detector. For frequency band 9KHz to 150KHz, the bandwidth of the field strength meter (R&S Test Receiver ESHS30) is set at 200Hz. For frequency band 150KHz to 30MHz, the bandwidth is set at 10KHz.


All the test results are listed in Section 5.7.



5.7. Test Results

PASS

The frequency range from 9KHz to 30MHz is investigated.


As the peak value is too low against the limit, so the Quasi-peak value has been omitted.
Please refer to the following page.





6. HARMONIC CURRENT EMISSION TEST

6.1. Block Diagram of Test Setup



6.2. Test Standard

EN 61000-3-2:2014

6.3. Operating Condition of EUT

6.3.1. Setup the EUT as shown in Section 6.1.

6.3.2. Turn on the power of all equipments.

6.3.3. Let the EUT work in test mode (ON) and test it.

6.4. Test Procedure

The power cord of the EUT is connected to the output of the test system. Turn on the Power of the EUT and use the test system to test the harmonic current level.

6.5. Test Results

N/A



7. VOLTAGE FLUCTUATIONS & FLICKER TEST

7.1. Block Diagram of Test Setup

Same as Section 6.1..

7.2. Test Standard

EN 61000-3-3: 2013

7.3. Operating Condition of EUT

Same as Section 6.3.. The power cord of the EUT is connected to the output of the test system. Turn on the power of the EUT and use the test system to test the harmonic current level.

Flicker Test Limit


Test items	Limits
Pst	1.0
dc	3.3%
dmax	4.0%
dt	Not exceed 3.3% for 500ms

7.4. Test Results

N/A

8. ELECTROSTATIC DISCHARGE TEST

8.1. Block Diagram of ESD Test Setup



8.2. Test Standard

EN 61547:2009 (EN61000-4-2:2009)
Severity Level 3 for Air Discharge at 8KV
Severity Level 2 for Contact Discharge at 4KV

8.3. Severity Levels and Performance Criterion

8.3.1. Severity level

Level	Test Voltage Contact Discharge (KV)	Test Voltage Air Discharge (KV)
1.	2	2
2.	4	4
3.	6	8
4.	8	15
X.	Special	Special

8.3.2. Performance criterion: B

8.4. EUT Configuration on Test

The configuration of EUT are listed in Section 3.4.

8.5. Operating Condition of EUT

8.5.1. Setup the EUT as shown in Section 8.1..

8.5.2. Turn on the power of all equipments.

8.5.3. Let the EUT work in test mode (Working Mode) and test it.

8.6. Test Procedure

8.6.1. Air Discharge:

This test is done on a non-conductive surfaces. The round discharge tip of the discharge electrode shall be approached as fast as possible to touch the EUT.

After each discharge, the discharge electrode shall be removed from the EUT.

The generator is then re-triggered for a new single discharge and repeated 10 times for each pre-selected test point. This procedure shall be repeated until all the air discharge completed.

8.6.2. Contact Discharge:

All the procedure shall be same as Section 8.6.1. except that the tip of the discharge electrode shall touch the EUT before the discharge switch is operated.

8.6.3. Indirect discharge for horizontal coupling plane

At least 20 single discharges shall be applied to the horizontal coupling plane, at points on each side of the EUT. The discharge electrode positions vertically at a distance of 0.1m from the EUT and with the discharge electrode touching the coupling plane.

8.6.4. Indirect discharge for vertical coupling plane

At least 20 single discharge shall be applied to the center of one vertical edge of the coupling plane. The coupling plane, of dimensions 0.5m X 0.5m, is placed parallel to, and positioned at a distance of 0.1m from the EUT. Discharges shall be applied to the coupling plane, with this plane in sufficient different positions that the four faces of the EUT are completely illuminated.

8.7. Test Results

PASS

Please refer to the following page.




Electrostatic Discharge Test Results

Shenzhen BCTC Technology Co., Ltd.

Applicant	: ShenZhen JMK Technology Co., ltd	Test Date	: Feb. 10, 2015	
EUT	: LED Strip	Temperature:	25℃	
M/N	: KS01-2835-72LED	Humidity	: 53%	
Power Supply	: DC24V			
Test Engineer	: Snow Zeng			
Air Discharge: ± 8KV				
Contact Discharge: ± 4KV # For each point positive 25 times and negative 25 times discharge				
Test Points	Air Discharge	Contact Discharge	Performance Criterion	Result
Others Slot of the EUT	±2,4,8KV	N/A	B	PASS
COVER	±2,4,8KV	N/A	B	PASS
VCP	N/A	±2,4 KV	B	PASS
HCP	N/A	±2,4 KV	B	PASS

9. RF FIELD STRENGTH SUSCEPTIBILITY TEST

9.1. R/S Test Setup



9.2. Test Standard

EN 61547:2009 (EN 61000-4-3: 2006+A1:2008+A2:2010)
Severity Level 2 at 3V / m

9.3. Severity Levels and Performance Criterion

9.3.1. Severity level

Level	Field Strength V/m
1.	1
2.	3
3.	10
X.	Special

9.3.2. Performance criterion : A

9.4. EUT Configuration on Test

The configuration of EUT are listed in Section 3.5..



9.5. Operating Condition of EUT

Setup the EUT as shown in Section 9.1.. The operating condition of EUT are listed in section 3.5.

9.6. Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above the ground. The EUT is set 3 meters away from the transmitting antenna which is mounted on an antenna tower. Both horizontal and vertical polarization of the antenna are set on test. Each of the four sides of EUT must be faced this transmitting antenna and measured individually.

In order to judge the EUT performance, a CCD camera is used to monitor the EUT.

All the scanning conditions are as follows :

Condition of Test	Remarks
1. Fielded Strength	3 V/m (Severity Level 2)
2. Radiated Signal	Modulated
3. Scanning Frequency	80 - 1000 MHz
4. Sweeping time of radiated	0.0015 decade/s
5. Dwell Time	1 Sec.

9.7. Test Results

PASS

Please refer to the following page.




RF Field Strength Susceptibility Test Results

Shenzhen BCTC Technology Co., Ltd.

Applicant: ShenZhen JMK Technology Co., ltd			Test Date : Feb. 10, 2015
EUT : LED Strip			Temperature : 25℃
M/N : KS01-2835-72LED			Humidity : 53%
Field Strength: 3 V/m			Criterion: A
Power Supply: DC24V			Frequency Range: 80 MHz to 1000 MHz
Test Engineer: Snow Zeng			
Modulation: ☒ AM ☐ Pulse ☐ none 1 KHz 80%			
Test Mode : On			
	Frequency Range : 80-1000MHz		
Steps	1 %		
	Horizontal	Vertical	Result
Front	A	A	Pass
Right	A	A	Pass
Rear	A	A	Pass
Left	A	A	Pass

10. ELECTRICAL FAST TRANSIENT/BURST IMMUNITY TEST

10.1 Block Diagram of EUT Test Setup



10.2 Test Standard

EN61547: 2009 (EN61000-4-4:2012)

Severity Level 2 at 1KV

10.3 Severity Levels and Performance Criterion

Severity Level 2 at 1KV, Pulse Rise time & Duration: 5 nS / 50 nS

Severity Level:

Open Circuit Output Test Voltage $\pm 10\%$		
Level	On power ports	On I/O(Input/Output) Signal data and control ports
1.	0.5KV	0.25KV
2.	1KV	0.5KV
3.	2KV	1KV
4.	4KV	2KV
X.	Special	Special

Performance criterion: B

- The apparatus shall continue to operate as intended during and after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended.
- The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. The performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- Temporary loss of function is allowed, provided the function is self-recoverable or can be restored by the operation of the controls.

10.4 EUT Configuration on Test

The following equipments are installed on Electrical Fast Transient/Burst Immunity test to meet EN 61547:2009, EN 61000-4-4:2012, requirement and operating in a manner which tends to maximize its emission characteristics in a normal application. The configuration of EUT is the same as used in conducted emission test.

Please refer to Section 3.6.

10.5 Operating Condition of EUT

Same as conducted emission measurement, which is listed in Section 3.6 except the test setup replaced by Section 10.1.

10.6 Test Procedure

EUT shall be placed 0.8m high above the ground reference plane which is a min.1m*1m metallic sheet with 0.65mm minimum thickness. This reference ground plane shall project beyond the EUT by at least 0.1m on all sides and the minimum distance between EUT and all other conductive structure, except the ground plane beneath the EUT, shall be more than 0.5m

10.6.1. For input and output AC power ports:

The EUT is connected to the power mains by using a coupling device which couples the EFT interference signal to AC power lines. Both polarities of the test voltage should be applied during compliance test and the duration of the test is 2 minutes.

10.6.2. For signal lines and control lines ports:

It's unnecessary to measure.

10.6.3. For AC input and DC output power ports:


It's unnecessary to measure

10.7 Test Results

N/A

11. SURGE TEST

11.1. Surge Test Setup



11.2. Test Standard

EN 61547:2009 (EN61000-4-5:2014)
Severity Level 2 for Line to Neutral at 1.0KV

11.3. Severity Levels and Performance Criterion

11.3.1. Severity level

Severity Level	Open-Circuit Test Voltage KV
1	0.5
2	1.0
3	2.0
4	4.0
*	Special

Performance criterion : **C**

11.4. EUT Configuration on Test

The configuration of EUT are listed in Section 3.7.

11.5. Operating Condition of EUT

11.5.1. Setup the EUT as shown in Section 11.1.

11.5.2. Turn on the power of all equipments.

11.5.3. Let the EUT work in test mode (Working Mode) and test it.



11.6. Test Procedure

- 1) Set up the EUT and test generator as shown on Section 11.1
- 2) For line to line coupling mode, provide a 0.5KV 1.2/50us voltage surge (at open-circuit condition) and 8/20us current surge to EUT selected points.
- 3) At least 5 positive and 5 negative (polarity) tests with a maximum 1/min repetition rate are conducted during test.
- 4) Different phase angles are done individually.
- 5) Record the EUT operating situation during compliance test and decide the EUT immunity criterion for above each test.

11.7. Test Results

N/A


12. INJECTED CURRENTS SUSCEPTIBILITY TEST

12.1 Block Diagram of EUT Test Setup

12.1.1. Block Diagram of EUT Test Setup



12.1.2. Block Diagram of Test Setup



12.2 Test Standard

EN 61547:2009 (EN 61000-4-6:2014)

12.3 Severity Levels and Performance Criterion

Severity Level 2: 3V(rms), 150KHz ~ 80MHz

Severity Level:

Level	Field Strength V
1.	1
2.	3
3.	10
X.	Special

Performance criterion: A

- A. The apparatus shall continue to operate as intended during and after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended.
- B. The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. The performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- C. Temporary loss of function is allowed, provided the function is self-recoverable or can be restored by the operation of the controls.

12.4 EUT Configuration on Test

The configuration of EUT is the same as used in conducted emission test. Please refer to Section 3.8.

12.5 Operating Condition of EUT

Same as conducted emission test, which is listed in Section 3.5 except the test set up replaced as Section 12.1.

12.6 Test Procedure

- 1) Set up the EUT, CDN and test generator as shown on section 12.1
- 2) Let EUT work in test mode and measure.
- 3) The EUT and supporting equipments are placed on an insulating support 0.1m high above a ground reference plane. CDN (coupling and decoupling device) is placed on the ground plane at above 0.1-0.3m from EUT. Cables between CDN and EUT are as short as possible, and their height above the ground reference plane shall be between 30 and 50 mm (where possible).
- 4) The disturbance signal described below is injected to EUT through CDN.
- 5) The EUT operates within its operational mode(s) under intended climatic conditions after power on.
- 6) The frequency range is swept from 150KHz to 80MHz using 3V signal level, and with the disturbance signal 80% amplitude modulated with a 1KHz sine wave



- 7) The rate of sweep shall not exceed 1.5×10^{-3} decades/s. Where the frequency is swept incrementally, the step size shall not exceed 1% of the start and thereafter 1% of the preceding frequency value.
- 8) Recording the EUT operating situation during compliance test and decide the EUT immunity criterion for above each test.


12.7 Test Result

N/A


13. MAGNETIC FIELD IMMUNITY TEST

13.1 Block Diagram of Test Setup

13.1.1 Block Diagram of the EUT



13.1.2 Block Diagram of Test Setup



13.2 Test Standard

EN 61547:2009, EN61000-4-8:2010

Severity Level 2 at 3A/m

13.3 Severity Levels and Performance Criterion

13.3.1 Severity level

Level	Magnetic Field Strength A/m
1.	1
2.	3
3.	10
4.	30
5.	100
X	Special

13.3.2 Performance criterion: B

- A. The apparatus shall continue to operate as intended during and after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended.
- B. The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended. The performance level may be replaced by a permissible loss of performance. During the test, degradation of performance is however allowed.
- C. Temporary loss of function is allowed, provided the function is self-recoverable or can be restored by the operation of the controls.

13.4 EUT Configuration on Test

The configuration of EUT is listed in Section 3.9.

13.5 Operating Condition of EUT

Same as conducted emission test, which is listed in Section 3.5 except the test set up replaced as Section 13.1.

13.6 Test Procedure


The EUT shall be subjected to the test magnetic field by using the induction coil of standard dimensions (1m*1m) and shown in Section 10.1. The induction coil shall then be rotated by 90° in order to expose the EUT to the test field with different orientations.

13.7 Test Results

N/A

14. VOLTAGE DIPS AND INTERRUPTIONS TEST

14.1 Voltage Dips and Interruptions Test Setup



Remark: Combination wave generator and decoupling network are included in test generator.

14.2 Test Standard

EN 61547:2009 (EN61000-4-11:2004)

14.3 Severity Levels and Performance Criterion

14.3.1 Severity level

Test Level %UT	Voltage dip and short interruptions %UT	Duration (in period)
0	100	250p
40	60	5p
70	30	0.5p

Performance criterion : C & B

14.4 EUT Configuration on Test

The configuration of EUT are listed in Section 3.10.

14.5 Operating Condition of EUT

14.5.1 Setup the EUT as shown in Section 14.1.

14.5.2 Turn on the power of all equipments.

14.5.3 Let the EUT work in test mode and test it.



14.6 Test Procedure

- 14.6.1 Set up the EUT and test generator as shown on Section 14.1.
- 14.6.2 The interruptions is introduced at selected phase angles with specified duration.
- 14.6.3 Record any degradation of performance.


14.7 Test Result

N/A


15. RADIATION EMISSION TEST

15.1 Block Diagram of Test Setup

15.1.1. Block Diagram of EUT Test Setup



15.1.2. Anechoic Chamber Setup Diagram



15.2 Test Standard

EN 55015: 2013

15.3 Radiation Limit

Frequency MHz	Distance (Meters)	Field Strengths Limits dB(μ V)/m
30 ~ 230	3	40.0
230 ~ 300	3	47.0

Remark:

- (1) Emission level (dB(μ V)/m) = 20 log Emission level (μ V/m)
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance refers to the distance in meters between the measuring instrument, antenna and the closed point of any part of the device or system.

15.4 EUT Configuration on Test

The EN55015 regulations test method must be used to find the maximum emission during radiated emission test.

The configuration of EUT is the same as used in conducted emission test.

Please refer to Section 3.11.

15.5 Operating Condition of EUT

Same as conducted emission test, which is listed in Section 2.2 except the test set up replaced as Section 15.1.

15.6 Test Procedure

The EUT and its simulators are placed on a turned table that is 0.8 meter above the ground. The turned table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna that is mounted on the antenna tower. The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated biconical and log periodical antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on test. In order to find the maximum emission levels, the interface cable must be manipulated according to EN55015 on radiated emission test.

The bandwidth setting on the field strength meter (R&S Test Receiver ESHS30) is set at 120KHz.

The frequency range from 30MHz to 300MHz is checked.

15.7 Test Result

PASS

Please refer to the following page.



Address: No.101, Yousong Road, Longhua New District,
Shenzhen, Guangdong P.R.China
Tel: 400-788-9558

Radiated Emission Measurement


File: 3

Data: #169

Date: 2015/02/06

Time: 13:54:01

80.0 dBuV/m



Site: 966 BCTC Chamber #1

Polarization: **Horizontal**

Temperature: 26

Limit: EN55015_03_QP

Power: DC 24V

Humidity: 55 %

EUT: LED Strip

Distance: 3m

M/N: KS01-2835-72LED

Mode: Working

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		35.9850	27.76	-8.59	19.17	40.00	-20.83	QP		
2	*	53.9661	31.49	-10.95	20.54	40.00	-19.46	QP		
3		71.9650	31.85	-15.24	16.61	40.00	-23.39	QP		
4		153.1515	26.37	-12.85	13.52	40.00	-26.48	QP		
5		166.0050	26.64	-13.22	13.42	40.00	-26.58	QP		
6		179.9373	27.77	-14.33	13.44	40.00	-26.56	QP		

*: Maximum data x: Over limit !: over margin

倍测检测
BCTC TESTAddress: No.101, Yousong Road, Longhua New District,
Shenzhen, Guangdong P.R.China
Tel: 400-788-9558

Radiated Emission Measurement


File: 3

Data: #173

Date: 2015/02/06

Time: 13:58:09

80.0 dBuV/m



Site: 966 BCTC Chamber #1

Polarization: **Vertical**

Temperature: 26

Limit: EN55015_03_QP

Power: DC 24V

Humidity: 55 %

EUT: LED Strip

Distance: 3m

M/N: KS01-2835-72LED

Mode: Working

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		90.3902	41.13	-17.47	23.66	40.00	-16.34	QP		
2		97.3019	36.13	-16.78	19.35	40.00	-20.65	QP		
3	*	100.7212	44.42	-16.42	28.00	40.00	-12.00	QP		
4		119.7075	34.45	-14.74	19.71	40.00	-20.29	QP		
5		229.1507	35.10	-15.11	19.99	40.00	-20.01	QP		
6		290.4834	42.38	-12.83	29.55	47.00	-17.45	QP		

*:Maximum data x:Over limit !:over margin

16. APPENDIX I EUT PHOTO

EUT Photo 1




EUT Photo 2




EUT Photo 3



EUT Photo 4



17. APPENDIX II EUT TEST PHOTO



***** END OF REPORT *****