

Omni-directional Barcode Scanner XL-2024



- ⊙ Anti-scraping protection glass window
- ⊙ 32 bit CPU, with 5 mil optical resolution
- ⊙ Best choice for hypermarket, healthcare and manufacturing process control
- ⊙ Touch screen button to adjust the volume
- ⊙ 24 scan lines at a rate of 1,600 scans per second



Light Source	Visible Laser Diode 650nm	Size	L × W × H:152mm × 152mm × 75mm
Scan Pattern	24 lines 6 fields of 4 parallel lines	Weight	576g
Scan speed	1600 scans/s	Material	ABS+PC
Print Contrast	30% @ UPC/EAN 100%	Laser Class	Meet the Grade I National Criteria for Laser Safety
Minimum Resolution	5mil@PCS90%	Voltage	9 Volts
Depth of Field	0-200mm for 13 mil	Static Current	430mA
Host System Interfaces	USB, RS232, Keyboard Wedge	EMC	CE EN55022 B, FCC Part 15 Class B, VCCI, BSMI
Visual Indicators	Two color LED (blue & red)	Operating Temperature	- 0°C to 50°C
Beeper Operation	Programmable tone & volume	Storage Temperature	- 20°C to 60°C
Cable	Standard 2M straight	Humidity	5% to 95% relative humidity
Decoding Capability	UPC/EAN/JAN, UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39 (with full ASCII), Codabar (Nw7), Code 128 & EAN 128, Code 93, Interleaved 2 of 5 (ITF), Addendum 2 of 5, IATA Code, MSI/Plessey, Code 32 (Italian Pharmacode), RSS 14, RSS Limited, RSS Expanded, China post.		



SUNLUX IOT Technology (Guangdong) Inc.

Office Add: 4F, No.7, Kehui First Street, Science Road, Science City, Guangzhou, China

Tel: +86-20-32053765 Fax: +86-20-82115390 Site: www.xl-scan.com E-mail: sales@xl-scan.com