Model	Picture	Specification	Plug	certification
POWERCUBE SAC 2-layer Tower		AC OUTPUT:16A,250V,4000W ••Overload Protector16A 3 X 1.5mm²,extended core 1.5m	EU	CE,VDE,CB KC,KCC LVD ERP,ROHS
POWERCUBE SAC-3C1A 2-layer Tower 20W		AC OUTPUT 16A 250V,4000W DC OUTPUT USB-C1 / C2 /C3- USB-A C1/C2/C3:PD60 5V=3.0A,9V=2.22A,12V=1.67A,20W USB-A:QC 5V=3.0A,9V=2.0A,12V=1.5A,18W C1+C2+C3+A1 Total:5V=3.6A,18W 3 X 1.5mm²,extended core 1.5m	EU	CE,VDE,CB KC,KCC LVD ERP,ROHS
POWERCUBE SAC-3C1A 2-layer Tower 30W		AC OUTPUT 16A 250V,4000W DC OUTPUT USB-C1/C2 -USB-A PD3 5V=3.0A,9V=3.0A,12V=2.5A,15V=2.0A,20V =1.5A,30W PPS:3.3V~11V=3.0A,3.2V~ 16V=2.0A,32W AC 5V=3.0A,9V=3.0A,12V=2.5A,15V=2.0A,20V =1.5A,30W C1+C2=A Total:5V=3.6A,18W ••Overload Protector16A	EU	CE,VDE,CB KC,KCC LVD ERP,ROHS
POWERCUBE SAC-3C1A 2-layer Tower 20W		AC OUTPUT 16A 250V,4000W DC OUTPUT USB-C1 / C2 /C3- USB-A C1/C2/C3:PD60 5V=3.0A,9V=2.22A,12V=1.67A,20W USB-A:QC 5V=3.0A,9V=2.0A,12V=1.5A,18W C1+C2+C3+A1 Total:5V=3.6A,18W 3 X 1.5mm²,extended core 1.5m	EU	CE,LVD,ERP,ROHS
POWERCUBE SAC-3C1A 2-layer Tower 30W		AC OUTPUT 16A 250V,4000W DC OUTPUT USB-C1/C2/C3/USB-A PD3 5V=3.0A,9V=3.0A,12V=2.5A,15V=2.0A,20V =1.5A,30W PPS:3.3V~11V=3.0A,3.2V~ 16V=2.0A,32W AC 5V=3.0A,9V=3.0A,12V=2.5A,15V=2.0A,20V =1.5A,30W C1+C2+C3+A Total:5V=3.6A,18W ••Overload Protector16A 3 X 1.5mm²,extended core 1.5m	EU	CE,LVD,ERP,ROHS
POWERCUBE SAC-3C1A 2-layer Tower 45W		AC OUTPUT:16A,250V,4000W DC OUTPUT:USB-C1/C2/C3/C4+USB-A1/A2 DC OUTPUT:USB- C1/5V=3.0A,9V=3.0A,12V=3.0A,15V=3.0A, 20V=2.25A,45W USB-C2/:5V=3.0A USB-C3/:5V=3.0A USB-C4/:5V=3.0A USB-A1/:5V=3.0A USB-A2/:5V=3.0A USB-C1+USB-C2/USB-C3/USB-C4/USB- A1/USB-A2:30W+15W 3 X 1.5mm²,extended core 1.5m	EU	CE,LVD,ERP,ROHS
POWERCUBE SAC-3C1A 2-layer Tower 70W		AC OUTPUT:16A,250V,4000W DC OUTPUT:USB-C1/C2/C3+USB-A1 DC OUTPUT:USB- C1/5V=3.0A,9V=3.0A,12V=3.0A,15V=3.0A, 20V=3.5A,70W PPS:3V~21V=2.25A,5V~21V=3A USB-C2/:5V=3.0A USB-C3/:5V=3.0A USB-A1/:5V=3.0A USB-C1+USB-C2/USB-C3/USB-A1:45W+15W 3 X 1.5mm²,extended core 1.5m	EU	CE,LVD,ERP,ROHS
POWERCUBE SAC 2-layer Tower		AC OUTPUT:16A,250V,4000W ••Overload Protector16A 3 X 1.5mm²,extended core 1.5m	EU	CE,VDE,CB KC,KCC LVD ERP,ROHS
POWERCUBE SAC-3C1A 3-layer Tower 20W		AC OUTPUT 16A 250V,4000W DC OUTPUT USB-C1 / C2 /C3- USB-A C1/C2/C3:PD60 5V=3.0A,9V=2.22A,12V=1.67A,20W USB-A:QC 5V=3.0A,9V=2.0A,12V=1.5A,18W C1+C2+C3+A1 Total:5V=3.6A,18W 3 X 1.5mm²,extended core 1.5m	EU	CE,VDE,CB KC,KCC LVD ERP,ROHS
POWERCUBE SAC-3C1A 3-layer Tower 30W		AC OUTPUT 16A 250V,4000W DC OUTPUT USB-C1/C2/C3+USB-A PD3 5V=3.0A,9V=3.0A,12V=2.5A,15V=2.0A,20V =1.5A,30W PPS:3.3V~11V=3.0A,3.2V~ 16V=2.0A,32W AC 5V=3.0A,9V=3.0A,12V=2.5A,15V=2.0A,20V =1.5A,30W C1+C2+C3+A Total:5V=3.6A,18W ••Overload Protector16A 3 X 1.5mm²,extended core 1.5m	EU	CE,VDE,CB KC,KCC LVD ERP,ROHS
POWERCUBE SAC-3C1A 3-layer Tower 20W		AC OUTPUT 16A 250V,4000W DC OUTPUT USB-C1 / C2 /C3- USB-A C1/C2/C3:PD60 5V=3.0A,9V=2.22A,12V=1.67A,20W USB-A:QC 5V=3.0A,9V=2.0A,12V=1.5A,18W C1+C2+C3+A1 Total:5V=3.6A,18W 3 X 1.5mm²,extended core 1.5m	EU	CE,LVD,ERP,ROHS
POWERCUBE SAC-3C1A 3-layer Tower 30W		AC OUTPUT 16A 250V,4000W DC OUTPUT USB-C1/C2/C3+USB-A PD3 5V=3.0A,9V=3.0A,12V=2.5A,15V=2.0A,20V =1.5A,30W PPS:3.3V~11V=3.0A,3.2V~ 16V=2.0A,32W AC 5V=3.0A,9V=3.0A,12V=2.5A,15V=2.0A,20V =1.5A,30W C1+C2+C3+A Total:5V=3.6A,18W ••Overload Protector16A 3 X 1.5mm²,extended core 1.5m	EU	CE,LVD,ERP,ROHS
POWERCUBE SAC-3C1A 3-layer Tower 45W		AC OUTPUT:16A,250V,4000W DC OUTPUT:USB-C1/C2/C3/C4+USB-A1/A2 DC OUTPUT:USB- C1/5V=3.0A,9V=3.0A,12V=3.0A,15V=3.0A, 20V=2.25A,45W USB-C2/:5V=3.0A USB-C3/:5V=3.0A USB-C4/:5V=3.0A USB-A1/:5V=3.0A USB-A2/:5V=3.0A USB-C1+USB-C2/USB-C3/USB-C4/USB- A1/USB-A2:30W+15W 3 X 1.5mm²,extended core 1.5m	EU	CE,LVD,ERP,ROHS
POWERCUBE SAC-3C1A 3-layer Tower 70W		AC OUTPUT:16A,250V,4000W DC OUTPUT:USB-C1/C2/C3+USB-A1 DC OUTPUT:USB- C1/5V=3.0A,9V=3.0A,12V=3.0A,15V=3.0A, 20V=3.5A,70W PPS:3V~21V=2.25A,5V~21V=3A USB-C2/:5V=3.0A USB-C3/:5V=3.0A USB-A1/:5V=3.0A USB-C1+USB-C2/USB-C3/USB-A1:45W+15W 3 X 1.5mm²,extended core 1.5m	EU	CE,LVD,ERP,ROHS