

MODEM / NULL MODEM CABLE

MODEM CABLE:DB25 M / DB9 F

ITEM No.	LENGTH	SPEC.
261201-X	X (1-10M)	UL2464 9CORES

WIRING	
DB9 F	DB25 M
1	8
2	3
3	2
4	20
5	7
6	6
7	4
8	5
9	22
SHELL	SHELL



NULL MODEM CABEL:DB9 / DB9 (9 CORES)

M/F	PIN	F/F	SPEC.
261202 -X		261204 -X	UL2464 9CORES

WIRING	
DB9	DB9
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
SHELL	SHELL



NULL MODEM CABLE:DB25 / DB25

F/F	M/F	SPEC.
261205-X	261207-X	UL2464 9CORES

WIRING	
DB25	DB25
1	1
2	3
3	2
4	4
5	5
-	-
-	-
25	25
SHELL	SHELL



NULL MODEM CABEL: DB9 / DB9 (8 CORES)

M/F	PIN	F/F	SPEC.
261203 -X		261205-X	UL2464 8CORES

WIRING	
DB9	DB9
2	3
3	2
4	1,6
1	4
6	4
5	5
7	8
8	7
SHELL	SHELL



NULL MODEM CABLE:DB25 / DB25

ITEM NO.	SPEC.
261208-X	UL2464 8CORES

WIRING	
DB25	DB9
2	2
3	3
4	8
5	7
7	5
6,8	4
20	1,6
1	SHELL



QUALITY FEATURE:

- Cable Material with UL2464 certificate
- Fully Shielded Cable
- Each PC process signal test to assure signal transfer well
- RoHS Compliance

ADDITIONAL FEATURE

Packing	We can offer printed poly bag and blister packing. If you request, we can specially make packing under your design.
Adaptor	We are with completed adaptors and mini Genders for your choosing

INFORMATION

1. We treat without ferrite cores as regular. If you need Ferrite Cores, please inform us.
2. We treat Black Color as regular. If you need other colors, please inform us.



DB9M / DB9M
 DB9M / DB9F
 DB9F / DB9F
 DB25M / DB25M
 DB25M / DB25F
 DB25F / DB25F
 HDB15M / HDB15M
 HDB15M / HDB15F
 HDB15F / HDB15F

MINI GENDER ADAPTOR