

RoHS

SPECIFICATIONS

PERFORMANCE

信号端子 Current Rating: 2A

电源端子 Current Rating: 25A

Insulation Resistance: 500MΩ

Withstang Volt: 175V AC/minute

Oprating Temperature: -55°C to +125°C

Material

Contact: Phosphor Bronze Gold-Plated

Housing: LCP

Max. Processing Temp: 230°C for 30-60 seconds
(260°C for 10 seconds)

Mating Draw (Ref)

A-A SECTION

P.C.B Layout

Ordering Information

HC-BTB50 - F 060 040 XX F X 01

F=Female No.of pins 20P~100P Plastic Hight 040=4.06mm Contact Plating G0:Gold Flash G1:3U" Gold G2:5U" Gold G3:10U" Gold G4:15U" Gold S0:1.5U" Gold/Tin S1:3U" Gold/Tin Insulator Material Option F=BK-LCP Packing T:Tube R:Reel

OPERATION

X.X ±0.30

X.XX ±0.20

X.XXX ±0.10

Angle ±3°

DIM TOL

DRAW

Lu jin ying

CHECK

APPROVE

SCALE

FIT

UNIT

mm

SIZE

A4

SHEET

1/1

PROJ.

◆

HECON

东莞市禾康电子有限公司
DONGGUAN HECON ELECTRONICS CO.,LTD

PART NO.

HC-BTB50-F060040XXFX01

TITLE:

0.5mm BTB 60Pin H4.06 Female

