

HSPOS TECHNOLOGY LIMITED

5 floor, A1 building, Nanshui Industrial Park, Sanjiao
Town, Zhongshan City, Guangdong Province, China
Tel +86 0760-85402097 Fax +86 0760-85402097

Website: www.hsprinter.com

Email: mikepeng@hsprinter.com



HS-K35 3" Embedded Thermal Printer

Features:

Support ESC/POS Command

Support Windows, Linux, Android SDK DEMO

Good price and Short delivery lead time

Factory/Manufacture with engineer team, able to do OEM&ODM

SUPPORT USB+RS232/ TTL+ Bluetooth interface.

Support Cash box Interface.


Support Big diameter roller paper more than the 60mm

Support Simplified Chinese, Traditional Chinese, English and other 45 kinds of international characters.



Applications:

Taximeter, Car tachograph, Self service, Ticket vending machine, Medical measuring instrument, Food tester, Weighing device, Electronic measuring instrument, Gas station, Factory equipment and many more



HSPOS TECHNOLOGY LIMITED
 5 floor, A1 building, Nanshui Industrial Park, Sanjiao
 Town, Zhongshan City, Guangdong Province, China
Tel +86 0760-85402097 **Fax** +86 0760-85402097
 Website: www.hsprinter.com
 Email: mikepeng@hsprinter.com



Specifications:

Printing Method	Thermal
Dots/line	640 dots/line
Resolution	203DPI
Printing Width(mm)	72mm
Paper Width(mm)	80mm
Paper Thickness(μm)	56-150
Paper diameter	MAX (60MM)
Feed Resolution(mm)	0.125
Interface	USB+RS232/ TTL+ Bluetooth/USB+ Parallel+Bluetooth
Installed size	99.6*105.5mm
W x D x H(mm)	105.5x111.5x75.8mm(L*W*H)
Weight(g)	600g
Head temperature detection	Thermistor
Operation voltage (V)	12V±10%
UTF-8	Support
Command	ESC/POS
Graph Printing	Support different density Graph, raster bitmap and download bitmap
Language	Simplified Chinese, Traditional Chinese, English and other 45 kinds of international characters
Barcode	1D Barcode UPC-A, UPC-E, EAN-8, CODE39, ITF; CODE128, CODE93, QR CODE
Chinese	GB1803024X24
Western	ASCII 9*17, 12*24
Logical voltage(V)	5±0.25
Formfeeding motor voltage(V)	24±10%
Auto cutting motor voltage(V)	24±10%
Detection voltage (V)	5±0.25
Abrasion resistance	100 km
Operating temperature(°C)	0 to 50 (no condensation)
Operating humidity(RH)	10% to 80% (no condensation)
Storage temperature(°C)	-25 to 70 (no condensation)
Storage humidity(RH)	5% to 95% (no condensation)