

Specification

Model Number	GM-VTS30A-G-F
DSP	KM01N-C
Operating system	Android, IOS
APP:	V380 PRO
Sensor:	1/3" Progressive Scan CMOS (SC2337X*3)
Video compressed format:	H.265/12fps
Resolution:	1920*3240
4G Network :	4G-BAND1/3/5/8/38/39/40/41
Detection method:	PIR + Radar dual induction detection
Detection distance:	0~12M
Detection angle:	80°+80°+80°
Alarm method:	Double induction confirmation and push alarm information mobilephone
Pan-tilt:	Big PTZ: Horizontal: 355 °, vertical: 90°, Small PTZ: Horizontal: 180°, vertical: 90°
Rotate speed	Horizontal 55°/seconds, vertical 40°/seconds
IR Leds	Right/Left: 4pcs Dual Core LED, Middle: 4pcs white light+4pcs Dual Core LED + 50
Full color night vision:	minimum illumination 0.00001LUX
Infrared Led:	Infrared LED distance: 30M ,effective distance :10M
White Led:	White LED distance: 30M, effective distance :10M
Built-in speaker:	3W
Built-in microphone:	Audio pick-up eara about 20M
Lens:	fixed-focus 4mm+4mm+4mm
Cloud storage:	Cloud Storage (Alarm video)
Local storage:	TF card (Max 128G)
power supply mode :	solar panel + 3.7V 18650 battery
Solar panel power:	16W
Battery capacity	Built-in 16000mah battery

Operating power	daytime: 350-400ma,Night time:500-550ma
Standby power	5 mA
work environment:	IP66 Waterproof,can use indoor and outdoor
Working temperature:	-30°~+50°
Working humidity:	0%~80%RH
Color box	36.3*25.2*24.3cm
Carton size	77.5*38*51.5cm
Carton quantity	6pcs.
Weight	16.7KG