

Panel Printer HCC-E3

Feature

- 1.Easy paper loading
- 2.Low noise thermal printing
- 3.Support RS232 or parallel interface
- 4.Front panel makes paper replacement easily
- 5.Easily embedded to any kind of instruments and meters

Specification

Printing Method	Thermal Line
Resolution	8 dots/mm, 384 dots/line
Effective Printing Width	48mm
Printing Speed	100mm/s
Character Set	ASCII, GB18030(Chinese), BIG5
Print Font	ANK: 9×24, 12×24
Self-defined Character	Yes
Character Per Line	32
Graphic	Support bitmap downloading
Paper End Sensor	Yes
Paper width	57.5± 0.5mm
Paper roll diameter	60mm (Max.)
MCBF	5 million lines
Auto cutter type	Guillotine
Auto cutter life	5,000,000 cuts
Auto cutter method	Partial cut
Interface	RS-232/Parallel/USB/RS-485
Paper supply method	Drop-in Easy Loading
Power supply:	DC9~24V±10%, 2A
Dimension (L x W x H)	109x101x68mm
Weight	185g
Operating Temp/Humidity	0-50°C/10%-80%
Storage Temp/Humidity	-20-60°C / 10%-90%
Installation port dimension (LxWxH)	103 x 95x 65mm



Picture

