

		MA-6060	MA-6120	MA-6240	MA-6360	MA-6480	MA-6650
Power source		AC:110V/60Hz and AC:220V/50Hz					
Power consumption		120W	240W	480W	720W	960W	1300W
Rated Output Power		60W	120W	240W	360W	480W	650W
Frequency response (AUX)		80 ~ 18KHz ± 3 dB, 1/2 rated output power					
DISTORTION(THD)		<0.3% at 1000Hz, 1/3 rated output power					
Output		100V/70V constant voltage output,and 4-16 Ω low impedance output					
Input Sensitivity of MIC		6MV(-42dB);Allowable deviation: ± 0.5 dB					
Input Sensitivity of AUX		250MV(-10dB);Allowable deviation: ± 0.5 dB					
Output Sensitivity of AUX		775MV(-2dB);Allowable deviation: ± 0.5 dB					
Tone Control	Treble	10KHz: ± 9 dB;Allowable deviation: ± 1.5 dB					
	Bass	10KHz: ± 9 dB;Allowable deviation: ± 1.5 dB					
S/N Ratio (AWeighted)	MIC	≥ 65 dB					
	AUX	≥ 75 dB					
Protection		AC Fuse, DC Voltage ,Overload and short circui					
Dimensions(WxHxD)		430L*360D*88H/mm					
net weight		7.8kg	9.1kg	11kg	13.5kg	14kg	18.5kg
Gross Weight		9.3kg	10.6kg	12.5kg	15.3kg	15.5kg	20kg