



Two-wire Intercom for Villa

Model DZ-3415

This is a digital 2-wire video door phone system, in which the outdoor station is connected with indoor monitors by 2 core wire.

A. Parameter

1) Outdoor Station

Working Voltage: DC 24~30V (powered by indoor monitor)

Working Current: <150mA(DC 24V)

Storage Temperature: -40°C ~ 70°C

Working Temperature: -25°C ~ 55°C

Dimension(L×W×H): 167×82×57mm

IP Grade: IP55

IK Grade: IK05

Housing: Aluminum alloy panel and Iron bottom box

Technique: Baking process

2) Camera

Camera Type: CMOS

Pixel: 2.0 MP

View Angle: 130°

Fill-in Light Type: infrared

3) Indoor Monitor

Display Screen: 7 inch

Resolution: 1024*600

Working Voltage: DC 24~48V

Working Current: <260mA(DC 24V)

Standby Current: <110mA(DC 24V)

Storage Temperature: -25°C ~ 70°C

Working Temperature: -10°C ~ 55°C

Dimension(L×W×H): 230×140×25mm



B. Functions:

1) HD Visual Intercom

--It provides high quality images and realistic sound effect to ensure accurate identification of visitors.

--It supports instant two-way intercom call between residents and visitors for confirming visit purpose.

2) Convenient Unlocking

--Visitors can press on the calling button on the outdoor station to get unlocking signal from indoor monitors manipulated by residents.

--It support access control with IC card.

3) Intelligent APP

--Residents can remotely conduct access control and real-time monitoring on smart phone through TUYA APP.

4) Two Relays

--It supports to unlock two doors, the main door and auxiliary door.