

Mobile Bluetooth Printer HCC-L51

Feature

1. LCD display
2. 1",2",3",4" Paper Size available
3. Super battery capability
4. Super diameter paper by outside bracket
5. Compatible with CPCL, ESC/POS command set

Specification

Printing Method	Thermal Line	
Resolution	8 dots/mm (203dpi)	
Effective Printing Width	104mm/100mm/72mm/48mm/37.5mm	
	101.5mm±0.5mm: 800dots/line	
	111.5mm±0.5mm:832dots/line	
Paper Width & Dots per line	44mm±0.5mm: 300dots/line 58mm±0.5mm: 384dots/line 79.5mm±0.5mm: 576dots/line 104mm±0.5mm: 800dots/line 112mm±0.5mm: 832dots/line	
Printing Speed	80mm/s (thermal paper); 50mm/s (label paper)	
Graph Printing	Diagram, downloaded bitmap supported	
Print Font	Chinese: 24×24; 16×16; ASCII: 9×24;12×24;18×16	
TPH	50km	
Barcode	1-Dimension	UPCA, UPCE, EAN13, EAN8, CODE39, ITF25, CODABAR, CODE9
		3, CODE128
	2-Dimension (reserved)	PDF417, QR CODE, DATA Matrix
Interface	Mini USB+Bluetooth Double Mould	
	Bluetooth2.0&Bluetooth4.0, one-to-many	
	BT or one-to-one BT optional) or WIFI (reserved)	
Command Set	ESC/POS & CPCL	
Other Functions	Paper-out alarm, Black-mark detection, Auto-sleep, LCD Display, Buzzer	
Paper Type	Thermal Paper, Black mark Paper(44mm or 58mm)and Label Paper	
Paper Roll Diameter	Max 40mm (extensible)	

Paper Thickness	0.06mm ~ 0.14mm
Battery& Charger	7.4V/2300mAh rechargeable Li-ion battery; 8.4V/800mA charger
Printing length for one charge	more than 120m (25% printing density)
Standby	more than 150hours
Paper Supply Method	Drop-in easy paper loading
Outline Dimension	140(L)X115(W)X51(H)mm
Weight	500g (not including paper)
Drop Resistance	1.5m

Picture

