

22⁺ YEARS EXPERIENCE

YOUR INSPIRATION TO SEALING SOLUTION



Product Details

Product Information

Material	Hardness (Shore A)	Temperature	Size	
			Standard Size	Available
NBR(Buna, Nitrile)	60~90	-40℃~110℃	AS-568(USA)	ID≤2000mm
FKM(VITON, FPM)	70~90	-20℃~220℃	JIS-B2401(Japan)	
EPDM	60~90	-45℃~150℃	DIN-3771(Germany)	CS≤40mm
Silicone(VMQ)	40~70	-55℃~204℃	BS-1516(UK)	
HNBR	60~90	-48℃~180℃	ISO3601(International)	
FFKM(FFKM, Kalrez)	70~90	-18℃~326℃	R(France)	
Resistance	Color	Certificate	Application	
Hydraulic Fluid Engine Oil Chemical Ozone & UV Steam & Hot Water Low Temperature High Temperature	Black Brown Red Green White Blue Clear Customized	ISO9001 ISO14001 TS16949 S G S. RoHS REACH	Auto Industry Construction Machinery Machine Tool Equipment Food Health Water Treatment Chemical Processing Hydraulic Pneumatic Industrial Manufacturing	



NBR O-Ring



FKM O-Ring



Silicone O-Ring



EPDM O-Ring



X-Ring



ED-Ring



O-Ring Kit



PTFE O-Ring



Flat Washer



Rubber Cord



Rubber Sheet



Custom Parts



O-RINGS



CUSTOM MOLDED RUBBER



GASKETS



MECHANICAL SEALS



HYDRAULIC SEALS



MACHINED PLASTICS



RADIAL SHAFT SEALS



RUBBER-TO-METAL BONDED



ENGINEERED COMPOUNDS