

HSPOS TECHNOLOGY LIMITED
5 floor, A1 building, Nanshui industrial
park, Sanjiao Town, Zhongshan City, Guangdong Province, China
Tel+86 0760-85546950 **Fax**+86 0760-85546950
Website: www.hsprinter.com
Email: mikepeng@hsprinter.com



HS-QR71 Series thermal Receipt Printer Datasheet

Function

Feature:

- Low-noise direct thermal printing method
- Printer control panel built-in ANK character or GB18030 Chinese character, thoroughly remove the uncommon words of anguish
- Fast printing speed, low noise
- Can support Max.39mm (diameter) paper roll, which is biggest paper roll of the same models.
- Optional serial interface (RS232C/TTL)/parallel/USB port
- Rich of graphics / curves / characters print function
- Easy paper loading structure
- Support 5V-9V/12V wide power voltage



Watermark

Application



Supermarket



Catering



Store



Tax



Bank



Medical care



Storage



Post

HSPOS TECHNOLOGY LIMITED
5 floor, A1 building, Nanshui industrial
park, Sanjiao Town, Zhongshan City, Guangdong Province, China
Tel +86 0760-85402097 **Fax** +86 0760-85402097
Website: www.hsprinter.com
Email: mikepeng@hsprinter.com



Parameters

ITEM	SPECIFICATION
Print method	thermal direct line printing
Paper loading method	easy paper loading
Paper width	58mm
Print width	48mm
Resolution ration	8dots/mm(384dots/line)
Life of printing head	50km
Printing speed	60mm/sec.; Max.:80MM/sec.(voltage 8.5V)
Character size	ANK: 9x17,12x24; GBK: 24x24
Chinese character fonts	GB18030: 12x24 or 24x24dots
Outline dimension (WxHxD mm)	111x65x57
Installation(WxH mm):	103x57
Embedded depth	50 mm
Paper roll specification	(width:58mm, Max. diameter:39mm)
Interface	RS232C/TTL/parallel/USB
Input power	DC5-9V or 12V
Operating temperature	5°C~50°C
Storage temperature	-20°C~60°C
Operating humidity	10°C~80°C
Storage humidity	10°C~90°C