

Red-black Speaker Cable

1. Multi-stranded/Flexible OFC, Copper, Tinned-copper wire conductor
2. Reliable Connection
3. High Quality New material of PVC Insulated
4. CE, RoHS SGS, ISO9001 Standard
5. Full 100M
6. Rated Voltage: 300/300V
7. Keep working under 70°C for long period operation

Model(size)	Specification Description	Outer Dia. (mm)	Jacket/sheath	Color
0.35mm ²	2CX20/0.15mm	O. D: 2.0X4.0	PVC	Transparent/Red-black
0.50mm ²	2CX28/0.15mm	O. D: 2.2X4.4	PVC	Transparent/Red-black
0.75mm ²	2CX42/0.15mm	O. D: 2.4X4.8	PVC	Transparent/Red-black
1.0mm ²	2CX57/0.15mm	O. D: 3.0X6.0	PVC	Transparent/Red-black
1.5mm ²	2CX85/0.15mm	O. D: 3.6X7.2	PVC	Transparent/Red-black
2.5mm ²	2CX7X20/0.15mm	O. D: 4.2X8.4	PVC	Transparent/Red-black
4.0mm ²	2CX7X32/0.15mm	O. D: 5.0X10.0	PVC	Transparent/Red-black
6.0mm ²	2CX7X48/0.15mm	O. D: 5.5X11.0	PVC	Transparent/Red-black

