



Shenzhen ELEBAO Technology Co.,Ltd

Experts in Android TV boxes, Intel mini PCs, digital signage and AV products

Add: 6F , Tower A , Zhihuichuangxin Certer Bldg, Qianjin Road, Xixiang, Bao'an District, Shenzhen, 518126 China

Email: sales2@elebaotec.com Contact: Ms Sylvia WhatsApp/Cell : +86-13434736011

www.elebaotec.com

MPI10 Barebone Gaming PC

Photo



CPU
(Processor)

Intel Comet Lake
Intel Whiskey Lake- U

i3-8145U(2core/4thred 2.1GHz-3.9Ghz 4M)
i5-8265U(4core/8thred 1.6GHz-3.9Ghz 6M)
i7-8565U(4core/8thred 1.8GHz-4.6Ghz 8M)
i3-10110U(2core/4thred 2.1GHz-4.1Ghz 4M)
i5-10210U(4core/8thred 1.6GHz-4.2Ghz 6M)
i7-10510U(4core/8thred 1.8GHz-4.9Ghz 8M)

GPU

Processor Graphics

i3-8145U(Intel UHD Graphics 300MHz-1.00GHz)
i5-8265U(Intel UHD Graphics 300MHz-1.10GHz)
i7-8565U(Intel UHD Graphics 300MHz-1.15GHz)
i3-10110U(Intel UHD Graphics 300MHz-1.0GHz)
i5-10210U(Intel UHD Graphics 300MHz-1.10GHz)
i7-10510U(Intel UHD Graphics 300MHz-1.15GHz)

BIOS

BIOS Type

AMI EFI BIOS

Supported Technologies

Auto Power On

Resume by Alarm (Scheduled startup)

Wake-up On LAN

Memory
&
Storage

Included Storage

0

Included Memory

0

Memory Type

DDR4-3200Mhz SO-DIMM

Max # of Memory
Channels

2

Max Memory Size

64GB

Storage
Expansion
Options

M.2 Card Slot (storage)

1 * M.2(SATA III / Nvme / intel Optane) 2280 SSD

SATA III Slot

1 * 2.5" 7mm SATA III SSD/HDD

Wireless
Configuration

M.2

Wifi5: Support 2.4&5.0G
Wifi6: Supported (Optional)

Bluetooth

Bluetooth 4.2

I/O
Specifications

Thunderbolt™ Ports

1 * Thunderbolt™ 3 type-C port, up to 40Gb/s speed. Support output 5120 x 3200@60Hz

USB Configuration

4 * USB 3.0, 2 * USB 2.0

HDMI

1 * HDMI 2.0. Support 4K*60Hz output. Max to 4096 x 2304 @60Hz

DP

1 * DP 1.4. Support t 4K*60Hz output. Max to 5120 x 3200 @60Hz

of Displays Supported

2

8111F LAN

1 * RJ45 100M/1000M

Audio

1 * 3.5mm Audio Jack (MIC/SPK Combo)

Other
Hardware

Fan

Built in non-noise Fan

Operation System	Windows	Windows 10 home / pro(64 bit)
	Linux	Linux Ubuntu 20.04LTS / Ubuntu18.04LTS
Power	Power Type	DC-In
	Power Adapter	19V/40W~65W(ϕ 5.5mm*2.5mm power connector)
Package Specifications	Material	Aluminum Alloy
	Vesa Bracket (Optional)	Vesa Bracket and screws for optional
	Color	Black
	Dimensions (W x D x H)	L126*W130*H45mm
	Color box	
	Carton	
Environment	Environment	0℃ ~ 40℃ (32 ℉ ~ 104 ℉) at 0.7m/s Air Flow
	Relative Humidity	75% @ 35℃ (non-condensing)

