

Product Type	<b>Diesel EN590</b>
Diesel EN590	<p data-bbox="824 233 1044 275"><b>Contaminants</b></p> <ul data-bbox="873 310 1414 533" style="list-style-type: none"><li data-bbox="873 310 1256 352">• <b>Water (max): 200 mg/kg</b></li><li data-bbox="873 352 1338 422">• <b>Total contamination (max): 24 mg/kg</b></li><li data-bbox="873 422 1252 464">• <b>Ash (max): 0.01 % mass</b></li><li data-bbox="873 464 1414 533">• <b>Carbon residue (on 10% distillation residue, max): 0.3 % mass</b></li></ul> <p data-bbox="824 569 997 611"><b>Distillation</b></p> <ul data-bbox="873 646 1360 758" style="list-style-type: none"><li data-bbox="873 646 1295 688">• <b>95% recovered at: <math>\leq 360</math> °C</b></li><li data-bbox="873 688 1360 758">• <b>Final boiling point:</b> controlled by distillation limits</li></ul> <p data-bbox="824 793 1003 835"><b>Flash Point</b></p> <ul data-bbox="873 871 1252 913" style="list-style-type: none"><li data-bbox="873 871 1252 913">• <b>Flash point (min): 55 °C</b></li></ul>