

H05VV-F

PVC Flexible Power Cords 聚氯乙烯电源软线

■产品说明

- 额定温度: 70℃
- 额定电压:300/500V
- 参考标准: DIN VDE 0281-5
- 导体使用绞合0.75~1.5mm²
- PVC 绝缘, 符合ROHS 环保标准
- PVC护套, 符合ROHS 环保标准
- 通过HD 405.1阻燃测试
- 使用标准绝缘厚度、易裁线、易剥皮
- 用于一般电子、电器电源连接线



■PRODUCT DESCRIPTION

- Rated temperature: 70℃
- Rated voltage: 300/500V
- Reference standard: DIN VDE 0281-5
- Stranded bare copper conductor 0.75~1.5mm²
- PVC insulation ,comply with ROHS environmental standard
- PVC jacket ,comply with ROHS environmental standard
- Passes HD 405.1 flame test
- Uniform insulation thickness to ensure easy stripping and cutting
- For general purpose use for power supply cord

■印字 MARKING

◁VDE▷ 40049557 H05VV-F () × () mm² 300/500V B&T (ZHANGZHOU) CABLE CO., LTD

■产品结构 CABLE CONSTRUCTION

编号	导体 CONDUCTOR			绝缘 INSULATION			护套 JACKET		最大导体 电阻 MAX. COND RESISTANCE Ω /km, (20	参考 重量 Approx. weight (g/m)	参考 包装 Standard packing (m)
	规格 SIZE	构造 CONSTRUCTION (No. /mm)	外径 DIA (mm)	芯数 NO.	厚度 THICKNESS (mm)	外径 DIA (mm)	厚度 THICKNESS (mm)	外径 O. D. (mm)			
H05VV0207524X X	0.75	24/0.20	1.13	2	0.6	2.35±0.10	0.8	6.3±0.20	26	40.63	150
H05VV0307524X X	0.75	24/0.20	1.13	3	0.6	2.35±0.10	0.8	6.7±0.20		48.42	100
H05VV0210032X X	1	32/0.20	1.31	2	0.6	2.50±0.10	0.8	6.6±0.20	19.5	48.4	100
H05VV0310032X X	1	32/0.20	1.31	3	0.6	2.50±0.10	0.8	7.1±0.25		64	100
H05VV0215030X X	1.5	30/0.25	1.58	2	0.7	3.00±0.10	0.8	7.6±0.25	13.3	48.4	100
H05VV0315030X X	1.5	30/0.25	1.58	3	0.7	3.00±0.10	0.8	8.3±0.30		64	100