

MODEL		GSP 48-60
RATED VOLTAGE (V)		- DC48
RATED CURRENT (A)		60
MAX.PV MODULES POWER(KW _p)		2.8
PV ARRAY INPUT CONTROLLER PATH		2
MAX.CURRENT EACH PV ARRAY (A)		30
STORAGE BATTERY OVER DISCHARGE PROTECTIVE VALUE (SETTABLE V)		43.2
STORAGE BATTERY OVER DISCHARGE RECOVERY (SETTABLE V)		49
STORAGE BATTERY OVER CHARGE PROTECTIVE VALUE (SETTABLE V)		58
LOAD OVER VOLTAGE PROTECTIVE VALUE (SETTABLE V)		65
LOAD OVER VOLTAGE RECOVERY VALU (SETTABLE V)		60
UN-LOAD CURRENT(mA)		< 100
VO LT AG E DR OP	PV ARRAY AND STORAGE BATTERY (V) STORAGE BATTERY AND LOAD (V)	0.3 0.1
TEMPERATURE COMPENSATION FACTOR (mV/℃)		0~5 (TUNABLE)
OPERATING TEMPERATURE (℃)		- 20~ + 50
WORKING ALTITUDE (m)		≤5000 (DECREASED THE CAPACTY AS GB/3859.2 WHEN ALTITUDE HIGHER THAN 1000MTS)
PROTECTIVE DEGREE		IP20
WALL MOUNTING TYPE SIZE (W×H×D mm)		482×132×270 (WITH HAND SHANK)