

		Winstars Product Specifications			Version		A0		
		ModelWS-UTA-01D			Page		1/1		
					Date		2016-09-18		
		Name			Type-C Thunderbolt 3 to Dual DisplayPort Display Adapter		Writer		唐龙
Picture tupia 图片					Features: 特点				
					• Supports 4K Dual Monitor Or 5K Single Monitor Resolutions At 60 Hz • Support pure DisplayPort, not DP++. • Incompatible with "passive" DisplayPort to HDMI/DVI/VGA adapters • Backward compatible with your high-definition 1080p displays, • Work more efficient by multitasking on two displays • Supports virtually any resolution between 720P and 4K, including the following: 5120x2880@60Hz (requires use of both DP ports) 4096x2160@60Hz 3840x2160@60Hz 3440x1080@60Hz 2560x1600@60Hz 2560x1440@60Hz 1920x1080 (1080P) @60Hz				
Title 标题					Type-C Thunderbolt 3 to Dual DisplayPort Display Adapter				
Description 介绍					Package content 标配		SYSTEM REQUIREMENT: 系统配置		
Unique classic black design, Thunderbolt 3 enables you to achieve the previously impossible feat of using a single port on your laptop to output dual 4K resolution at 60Hz to two independent displays. Won't drain system resources, you can work more efficiently from your laptop, so you can accomplish more in the same amount of time. Also you can have four times the screen space compared to 1080p.					1 x Type-C Thunderbolt 3 to Dual DisplayPort Display Adapter		Supports any operating system which has driver support for Thunderbolt 3. Currently, this is limited to Microsoft Windows . Non-Windows Operating Systems may obtain Thunderbolt 3 support in the future		
Specification 规格									
Hardware 硬件				Functions 功能		Exterior 外观			
Ports		Thunderbolt 3 Type-C , Dual Displayport		Working Standards	Laptop or Dssktop with Thunderbolt 3 Type-C port	Color		Black	
Button		NIL							
LED		Blue							
Chipset		JXL6540							
Flash		W25X20CLSNIG		Operating System Support	Currently, this is limited to Microsoft Windows				
SDRAM		NIL							
Power Supply		NIL							
Power Plug		NIL		Max Pixels		as showm in Features			
Power Consumption		2W		Max Charing Current(A)		NIL			
Rated Voltage/ requency /current									
Dimensions 尺寸				Certification 证书					
Unit Dimensions				CE-EMC	Able				
Weight		200g		CE-RTTE	Able				
Housing Material		ABS Plastic		CE-LVD	Able				
Shell color		Black		FCC DOC	Able				
Package Dimensions		Update later		FCC ID	Able				
Environmental 环境				ROHS	Able				
Operating Temperature		0°C~40°C		Reach	Able				
Storage Temperature		-10~70°C		3C	Able				
Relative Humidity(Operational)		10%~90%,noncondensing		Others 其他					
Relative Humidity(Storage)		10%~90%,noncondensing		Method		See Manual			
Drop test (1 Meters)		5 st		Performance		See Test Report			
Cycle work (hours)		24H		Reliability		See Test Report			