

FC/PC-SC/PC Multimode Simplex Fiber Optic Patch Cord**FR-FC/PC-SC/PC-MM-Sx****Features**

Low insertion loss and back reflection loss
Good Durability
Good exchangeability
High temperature stability
Standard: Telcordia GR-326-CORE

Applications

CATV / Metro
Active device termination
Telecommunication networks
Local Area Networks (LANs)
Data processing networks
Test equipment
Premise installations
Wide Area Networks (WANs)

Specifications

Insertion Loss: Typical $\leq 0.2\text{dB}$, Maximum $\leq 0.3\text{dB}$

Return Loss : $\geq 50\text{dB}$ (PC); $\geq 65\text{dB}$ (APC)

Repeatability: ≤ 0.1

Durability $\leq 0.2\text{dB}$ typical change, 1000 matings

Interchangeability: $\leq 0.2\text{dB}$

Tensile Strength : $>10\text{kg}$

Operating Temperature: $-40 \sim 85^{\circ}\text{C}$

Please contact us to get details.

Contact: Rose Ho

Tel: +86 -755-29340062 Fax: +86-755-83127301

E-Mail: rose@fiberroad.com.cn

MSN: fiberroad@hotmail.com

Skype: [fiberroadrose](https://www.skype.com/people/fiberroadrose)