

Model:
APP:
System structure:
Chip:
Resolution:
Sensor Resolution:
Lens:
View angle:
Pan-tilt:
Preset point quantity:
Video compression standard:
Video format:
Minimum illumination:
Electronic shutter:
Backlight compensation:
Noise reduction:
LED quantity:
Network:
Network connection:
Night vision:
Audio:
Network protocol:
Alarm:
Storage:
Power input:
Package:

Work environment:



SC02-W
V380 Pro
Embedded Linux system, ARM chip structure
ANKA KM01D
4MP
1/2.9" MIS2008*2
2*4MM
2*80°
Rotates Horizontal:355° Vertical: 90°
6
H.265/15FPS
PAL
0.01Lux@ (F2.0, VGC ON),0.Luxwith IR
Auto
Support
2D、3D
Bullet camera:6pcs white LED + 3pcs Infrared LED PTZ camera: 8pcs white LED + 6pcs Infrared LED
WIFI wireless transmission (support IEEE802.11b/g/n wireless protocol).
WIFI, AP Hotspot, RJ45 Network port
IR-CUT switch Automatic, about 5-8meters (It varies from environment) White Led can be remote control via APP:①Turn ON ②Turn OFF ③ Auto (In automatic mode, the infrared light will be turned ON after the IR-cut switch to night vision automatically , it can intelligently detected human body, and Turn ON/OFF the White light intelligently)
Built-in microphone and speaker, support two-way audio and real-time transmission. ADPCM audio compression standard, self-adapt to code stream
TCP/IP、DDNS、DHCP
①Motion detection and picture push ②AI Human intrusion Detection
TF Card (Max 128G) ; Cloud storage /Cloud disk (optional)
12V/2A (Including power supply)
Product size:23.5*14.9*18 weight:0.85kg, Carton Size:71*46*50cm ,weight:22kg.24pcs/ctn

Working temperature:-10℃ ~ + 50℃ Working Humidity: ≤95%RH