

	Winstars Product Specifications			Version	V1.0		
				Page	1/1		
	Model	WS-UTA02H			Date	2018.04.10	
Name	Type-C Thunderbolt 3 to Dual HDMI Display Adapter			Writer		Chen	
Picture tupia 图片				Features: 特点			
				• Supports Dual HDMI(2.0) displays at resolutions up to 4K@60Hz to your Thunderbolt 3 PC Computers,			
				• 40Gbps of bandwidth made possible by Intel's Thunderbolt 3 technology,			
				• Currently only Thunderbolt 3 systems from Apple, Dell, HP, and Lenovo meet this requirement,			
				• Backward compatible with your high-definition 1080p displays,			
				• Work more efficient by multitasking on two displays,			
				• Supports virtually any resolution between 720P and 4K, including the following:			
				4096x2160@60Hz			
				3840x2160@60Hz			
				3440x1080@60Hz			
				2560x1600@60Hz			
				2560x1440@60Hz			
				1920x1080 (1080P) @60Hz			
Title 标题							
Type-C Thunderbolt 3 to Dual HDMI Display Adapter							
Description 介绍				Package content 标配		SYSTEM REQUIREMENT: 系统配置	
Unique classic black design, Thunderbolt 3 enables you to achieve the previously impossible feat of using a single port on your laptop to output dual 4K resolution at 60Hz				1 x Type-C Thunderbolt 3 to Dual HDMI Display Adapter		Thunderbolt 3 systems from Apple, Dell, HP, and Lenovo meet this requirement	
to two independent displays. Won't drain system resources, you can work more efficiently from your laptop, so you can accomplish more in the same amount of time. Also you can have four times the screen space compared to 1080p.							
Specification 规格							
Hardware 硬件			Functions 功能		Exterior 外观		
Ports	Thunderbolt 3 Type-C , Dual HDMI (Compliant 2.0)		Working Standards	Laptop or Dssktop with Thunderbolt 3 Type-C port	Color	Apple Gray	
Button	NIL						
LED	Blue						
Chipset	JHL6540, TPS65983						
Flash	W25X20CLSNIG		Operating System Support	Currently, this is limited to Microsoft Windows & Mac Os			
SDRAM	NIL						
Power Supply	NIL						
Power Plug	NIL						
Power Consumption	2W		Max Pixels	as showm in Features			
Rated Voltage/ Frequency / Current	NIL		Max Charing Current(A)	NIL			
Dimensions 尺寸			Certification 证书				
Unit Dimensions	103 X 55X 20MM (L x H x W)		CE-EMC	Able	NO suitable		
Weight	Approx. 250g		CE-RTTE	Able			
Housing Material	Aluminum		CE-LVD	Able			
Shell color	Apple Gray		FCC DOC	Able			
Package Dimensions	163*123*33(L x H xW)		FCC ID	Able			
Environmental 环境			ROHS	Able			
Operating Temperature	0°C~40°C		Reach	Able			
Storage Temperature	-10~70°C		3C	Able			
Relative Humidity(Operational)	10%~90%,noncondensing		Others 其他				
Relative Humidity(Storage)	10%~90%,noncondensing		Method	See Manual			
Drop test (1 Meters)	5 st		Performance	See Test Report			
Cycle work (hours)	24H		Reliability	See Test Report			